Overview

HP ProDesk 400 G1 Desktop Mini Business PC



1. 3.5mm headphone output and microphone jacks
2. (2) Front USB 3.0 ports
3. Power button and PC status LED

Not Shown

Slots	(1) internal M.2 connector for optional wireless NIC (1) internal M.2 connector for optional SSD drive
Bays	(1) 2.5” internal storage drive bay
Rear I/O	(2) USB 2.0 ports (2) USB 3.0 ports (1) VGA video port; (1) DisplayPort with multi-stream video ports (1) RJ-45 network connector
VESA	Support for VESA 100mm mounting system on bottom of PC chassis

Overview

HP ProDesk 400 G1 Small Form Factor Business PC



1. Power button
2. PC status LED
3. 3.5” external drive bay; used for installing a Media Card Reader
4. (2) USB 2.0 ports (black)
5. (2) USB 3.0 ports (blue)
6. 3.5mm microphone jack
7. 3.5mm headphone output

Not Shown

Slimline drive bay supporting an optical disk drive (located behind removable bezel)

Slots	(1) PCI Express x16 graphics connectors (3) PCI Express x1 accessory connectors (1) USB 2.0 header for media card reader (1) Parallel port (optional)
Bays	(1) 2.5” internal storage drive bay (1) 3.5” internal storage drive bay
Rear I/O	(4) USB 2.0 ports (1) VGA video port; (1) DVI-D video port (1) RJ-45 network connector (1) RS-232 serial port; (1) RS-232 serial port (optional) 3.5mm audio in/out jacks PS/2 keyboard and mouse ports

Overview

HP ProDesk 400 G1 Microtower Business PC



1. Drive bay supporting an optical disk drive (optional)
2. Power button
3. PC status LED
4. (2) USB 3.0 ports (black)
5. (2) USB 2.0 ports (blue)
6. 3.5mm microphone jack
7. 3.5mm headphone output

Not Shown

5.25” External Drive Half-Height Drive Bay (located behind removable bezel)
3.5” external drive bay; used for installing a Media Card Reader

Slots	(1) PCI Express x16 graphics connectors (3) PCI Express x1 accessory connectors (1) USB 3.0 header for media card reader (1) Parallel port (optional)
Bays	(2) 3.5” internal storage drive bays
Rear I/O	(4) USB 2.0 ports (1) VGA video port; (1) DVI-D video port (1) RJ-45 network connector (1) RS-232 serial port (1) RS-232 serial (optional) 3.5mm audio in/out jacks PS/2 keyboard and mouse ports

Overview

At A Glance

- Choice of three chassis form factors: Desktop Mini, Small Form Factor and Microtower
- Small Form Factor and Microtower feature expandable, upgradable chassis and system board
- HP Desktop Mini chassis are space-saving and energy-efficient
- Intel® H81 Express chipset supporting Intel® 4th generation Core processors, featuring integrated Intel® HD Graphics
- HP developed and engineered UEFI BIOS supporting security, manageability and software image stability
- Realtek RTL8151GH-CG GbE LOM integrated network connection on Small Form Factor and Microtower ; Intel i217LM GbE LOM integrated network connection on Desktop Mini
- Up to 16GB DDR3 Synchronous Dynamic Random Access Memory (SDRAM)
- Multi-independent monitor support
- Discrete graphics options available for Small Form Factor and Microtower
- DTS Sound+™ audio management software
- Standard and high efficiency energy saving power supply options
- Wake from USB Keyboard (available for Desktop Mini only)
- Support for VESA 100mm mounting on bottom of Desktop Mini PC chassis
- Desktop Mini 400 is compatible with HP Desktop Mini Family Accessories
- ENERGY STAR® certified and EPEAT® Gold models

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Standard Features and Configurable Components

OPERATING SYSTEMS

Preinstalled When Purchased

Windows 8.1 Pro (64-bit)*
Windows 8.1 Pro for Education (64-bit)*
Windows 8.1 (64-bit)*
Windows 8.1 with Bing (64-bit)*
Windows 7 Professional (32-bit)*
Windows 7 Professional (64-bit)*
Windows 7 Professional (32-bit) (available through downgrade rights from Windows 8.1 Pro)**
Windows 7 Professional (64-bit) (available through downgrade rights from Windows 8.1 Pro)**
FreeDOS 2.0
Novell SUSE Linux Enterprise Desktop 11

*Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows functionality. See http://www.microsoft.com.
**This system is preinstalled with Windows 7 Professional software and also comes with a license and media for Windows 8.1 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

PROCESSORS

Intel® 4th Generation Core™ i7 Processors	DM	MT/SFF
Intel® Core™ i7-4790 Processor Up to 4.0 GHz Max. Turbo Frequency (3.6 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i7-4790s Processor Up to 4.0 GHz Max. Turbo Frequency (3.2 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i7-4770 Processor Up to 3.9 GHz Max. Turbo Frequency (3.4 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i7-4771 Processor Up to 3.9 GHz Max. Turbo Frequency (3.5 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i7-4770S Processor Up to 3.9 GHz Max. Turbo Frequency (3.1 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X

Standard Features and Configurable Components

	DM	MT/SFF
Intel® Core i7-4785T Up to 3.2 GHz Max. Turbo Frequency (2.2 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Core i7-4765T Up to 3.0 GHz Max. Turbo Frequency (2.0 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	

Intel® 4th Generation Core™ i5 Processors	**DM**	**MT/SFF**
Intel® Core™ i5-4690 Processor Up to 3.9 GHz Max. Turbo Frequency (3.5 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4690S Processor Up to 3.9 GHz Max. Turbo Frequency (3.2 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4590 Processor Up to 3.7 GHz Max. Turbo Frequency (3.3 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4590S Processor Up to 3.7 GHz Max. Turbo Frequency (3.0 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4570 Processor Up to 3.6 GHz Max. Turbo Frequency (3.2 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4570S Processor Up to 3.6 GHz Max. Turbo Frequency (2.9 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X

Standard Features and Configurable Components

	DM	MT/SFF
Intel® Core™ i5-4670 Processor Up to 3.8 GHz Max. Turbo Frequency (3.4 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4670S Processor Up to 3.8 GHz Max. Turbo Frequency (3.1 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4430 Processor Up to 3.2 GHz Max. Turbo Frequency (3.0 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4430s Processor Up to 3.2 GHz Max. Turbo Frequency (2.7 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i5-4590T Processor Up to 3.0 GHz Max. Turbo Frequency (2.0 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Core™ i5-4570T Processor Up to 3.6 GHz Max. Turbo Frequency (2.9 GHz base frequency) 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® 4th Generation Core™ i3 Processors	**DM**	**MT/SFF**
Intel® Core™ i3-4370 Processor Up to 3.8 GHz Base Frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4360 Processor Up to 3.7 GHz Base Frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X

Standard Features and Configurable Components

	DM	MT/SFF
Intel® Core™ i3-4350 Processor Up to 3.6 GHz Base Frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4160 Processor Up to 3.6 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4150 Processor Up to 3.5 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4340 Processor Up to 3.6 GHz Max. Turbo Frequency (3.6 GHz base frequency) 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4330 Processor Up to 3.5 GHz Max. Turbo Frequency (3.5 GHz base frequency) 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4130 Processor Up to 3.4 GHz Max. Turbo Frequency (3.4 GHz base frequency) 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Core™ i3-4360T Processor 3.2 GHz base frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Core™ i3-4350T Processor 3.1GHz base frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	

Standard Features and Configurable Components

	DM	MT/SFF
Intel® Core™ i3-4330T Processor 3.0 GHz base frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 4600 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Core™ i3-4160T Processor 3.1 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Core™ i3-4150T Processor 3.0 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Core™ i3-4130T Processor 2.9 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 4400 Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Pentium® Processors	**DM**	**MT/SFF**
Intel® Pentium® G3460 Processor Up to 3.5 GHz Base Frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Pentium® G3450 Processor Up to 3.4 GHz Base Frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Pentium® G3440 Processor Up to 3.3 GHz Base Frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Pentium® G3250 Processor Up to 3.2 GHz Base Frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate		X

Standard Features and Configurable Components

	DM	MT/SFF
Intel® Pentium® G3240 Processor Up to 3.1 GHz Base Frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate		X
Intel® Pentium® G3430 Processor Up to 3.3 GHz Max. Turbo Frequency (3.3 GHz base frequency) 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Pentium® G3420 Processor Up to 3.2 GHz Max. Turbo Frequency (3.2 GHz base frequency) 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Pentium® G3220 Processor Up to 3.0 GHz Max. Turbo Frequency (3.0 GHz base frequency) 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate		X
Intel® Pentium® G3450T Processor 2.9 GHz base frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Pentium® G3440T Processor 2.8 GHz base frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Pentium® G3420T Processor 2.7 GHz base frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Pentium® G3250T Processor 2.8 GHz base frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate	X	

Standard Features and Configurable Components

	DM	MT/SFF
Intel® Pentium® G3240T Processor 2.7 GHz base frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Pentium® G3220T Processor 2.6 GHz base frequency 3 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1600 MT/s data rate	X	
Intel® Celeron® Processors	**DM**	**MT/SFF**
Intel® Celeron® G1850 Processor 2.9 GHz base frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate		X
Intel® Celeron® G1840 Processor 2.8 GHz base frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate		X
Intel® Celeron® G1830 Processor 2.8 GHz base frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate		X
Intel® Celeron® G1820 Processor 2.7 GHz base frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate		X
Intel® Celeron® G1840T Processor 2.5 GHz base frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate	X	
Intel® Celeron® G1820T Processor 2.4 GHz base frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics Supports DDR3 memory up to 1333 MT/s data rate	X	

NOTE: Multi-Core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. 64-bit computing system required. Performance will vary

Standard Features and Configurable Components

depending on your hardware and software configurations. Intel's numbering is not a measurement of higher performance.

CHIPSET

Intel® 8 Series (H81 Express) Chipset

GRAPHICS

	DM	MT/SFF
Intel® HD Graphics on all models (integrated on processor)	**X**	**X**
AMD Radeon™ HD 8350 (1GB) FH PCIe x16		**MT only**
AMD Radeon™ HD 8350 (1GB) PCIe x16		**X**
AMD Radeon™ HD 8470 (2GB) FH		**MT only**
AMD Radeon™ HD 8490 (1GB) PCIe x16		**X**
NVIDIA® GeForce® GT630 (2GB) FH PCIe x16		**MT only**
NVIDIA® NVS™ 310 x16 1st (no cbl)		**X**
NVIDIA® NVS™ 315 (1GB) PCIe x1		**X**

ADAPTERS AND CABLES

	DM	MT/SFF
HP DMS-59 to Dual DisplayPort Cable		**X**
HP DMS-59 to Dual DVI Cable		**X**
HP DMS-59 to Dual VGA Cable		**X**
HP DisplayPort to DisplayPort Cable		**X**
HP DisplayPort to DVI-D Adapter	**X**	**X**
HP DisplayPort to HDMI 1.4 Adapter	**X**	**X**
HP DisplayPort to VGA Adapter	**X**	**X**
HP Serial Port Adapter		**X**
HP Parallel Port Adapter		**X**
HP DisplayPort Cable	**X**	**X**
HP USB to Serial Port Adapter	**X**	

STORAGE

NOTE: For storage, GB = 1 billion bytes, TB = 1 trillion bytes. Actual formatted capacity is less. Up to 26GB of system disk is reserved for system recovery software (for Windows 8.1).

SATA Drives	**DM**	**MT**	**SFF**
500 GB, 7.2K rpm, SATA 6.0 Gb/s, SMART IV, 3.5"			**X**
1 TB, 7.2K rpm, SATA 6.0 Gb/s, SMART IV, 3.5"		**X**	**X**
2 TB, 7.2K rpm, SATA 6.0 Gb/s, SMART IV, 3.5"		**X**	**X**
500GB 7200 RPM SATA 2.5 HDD	**X**		
500GB 7200 RPM SATA 2.5 2nd HDD	**X**		
SATA Self-Encrypting HDD			
500GB 7200 RPM SATA 2.5 SED HDD	**X**		
500GB 7200 RPM SATA 2.5 2nd SED HDD	**X**		

Standard Features and Configurable Components

Hybrid Drives	DM	MT	SFF
500 GB SATA 6G 2.5 (8GB cache) SSHD Drive (with 3.5" adapter when installed in SFF/MT	X	X	X
500 GB SATA 6G 2.5 2nd Drive (8 GB cache) SSHD Drive (with 3.5" adapter when installed in SFF/MT)	X	X	X
1 TB SATA 6G 2.5 (8 GB cache) SSHD Drive (with 3.5" adapter when installed in SFF/MT)	X	X	X
1 TB SATA 6G 2.5 2nd Drive (8 GB cache) SSHD Drive (with 3.5" adapter when installed in SFF/MT)	X	X	X

Solid State Drives	DM	MT	SFF
128 GB SATA 6G 2.5 SSD (with 3.5" adapter when installed in MT)	X	X	X
128 GB SATA 6G 2.5 2nd SSD (with 3.5" adapter when installed in SFF/MT)		X	X
120GB SATA 2.5 Non-SED SSD	X		
128GB SATA 2.5 SSD TLC Non-SED	X		X
120GB SATA 2.5 2nd Non-SED SSD	X		
120GB SATA 2.5 w/caddy Non-SED SSD	X		
120GB SATA 2.5 w/caddy 2nd Non-SED SSD	X		
128GB M.2 PCIe SSD	X		
180GB SATA 2.5 Non-SED SSD	X		
180GB SATA 2.5 2nd Non-SED SSD	X		
180GB SATA 2.5 w/caddy Non-SED SSD	X		
180GB SATA 2.5 2nd w/caddy Non-SED SSD	X		
256GB SATA 2.5 SSD	X		
256GB SATA 2.5 2nd SSD	X		
256GB SATA 2.5 SSD TLC Non-SED	X		X
500GB 2.5 FIPS 140-2 SED HDD	X		
500GB 2.5 FIPS 140-2 2nd SED HDD	X		

Self-encrypting Solid State Drive	DM	MT	SFF
120 GB SATA 2.5" Opal1 (SED) Solid State Drive	X		X
120 GB SATA 2.5" Opal1 (SED) Solid State Drive with caddy MT	X	X	
180 GB SATA 2.5" Opal1 (SED) Solid State Drive S	X		X
180 GB SATA 2.5" Opal1 (SED) Solid State Drive with caddy MT	X	X	
256 GB SATA 2.5" Self-Encrypting (SED) Solid State Drive (with 3.5" adapter when installed in MT)	X	X	X
256 GB SATA 2.5" 2nd Self-Encrypting (SED) Solid State Drive installed w/caddy		X	X
256GB SATA 2.5 2nd Opal2 SED SSD	X		
128GB SATA 2.5 Opal2 SED SSD	X		
128GB SATA 2.5 2nd Opal2 SED SSD	X		
256GB SATA 2.5 Opal2 SED SSD	X		

Optical Disc Drive	DM	MT	SFF
Blu-ray BDXL Writer		X	

Standard Features and Configurable Components

SuperMulti DVD Writer		X	
DVD-ROM		X	
Slim DVD-ROM			X
Slim BDXL Blu-ray Writer			X
Slim SuperMulti			X

Media Card Reader	**DM**	**MT**	**SFF**
15-in-1 USB2/3 Media Card Reader		X	X

Note: Super Multi DVD-RAM cannot read or write to 2.6GB Single Sided/5.2 GB Double Sided – Version 1.0 media. With Blu-Ray, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this Desktop PC. Don't copy copyright protected material.

MEMORY

Form Factor	**Type**	**Maximum**	**# of Slots**
Desktop Mini	DDR3 non-ECC up to 1600 MT/s	16 GB	2 SODIMM
Small Form Factor	DDR3 non-ECC Up to 1600 MT/s	16 GB	2 DIMM
Microtower	DDR3 non-ECC Up to 1600 MT/s	16 GB	2 DIMM

NOTE: For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system. Memory modules support data transfer rates up to 1600 MT/s; actual data rate is determined by the system's configured processor. See processor specifications for supported memory data rate.

NETWORKING/COMMUNICATIONS

Ethernet (RJ-45)	**DM**	**MT**	**SFF**
Realtek RTL8151GH-CG GbE LOM (standard on SFF and MT)		X	X
Intel i217LM GbE LOM	X		
Intel® Ethernet I210-T1 PCIe x1 Gb Network Interface Card (optional)		X	X

Wireless	**DM**	**MT**	**SFF**
Intel® Dual Band Wireless-N 7260 802.11 a/b/g/n PCI Express (optional)	X	X	X
HP WLAN 802.11 a/g/n 2x2 DualBand PCIe x1 Card (optional)		X	X

AUDIO/MULTIMEDIA

Feature	**DM**	**MT**	**SFF**
HD audio with Realtek ALC221 codec (all ports are stereo)	X	X	X
DTS Studio Sound™ audio management technology	X	X	X
Microphone and headphone front ports (3.5mm)	X	X	X
Line-out and Line-In rear Ports (3.5mm)		X	X
Multi-streaming capable	X	X	X

Standard Features and Configurable Components

Internal speaker (standard)	X	X	X

KEYBOARDS AND POINTING DEVICES

Keyboard	DM	MT	SFF
HP PS/2 Keyboard		X	X
HP USB Keyboard	X	X	X
USB Smart Card (CCID) Keyboard	X	X	X
HP USB and PS/2 Washable Keyboard	X	X	X
HP Wireless Keyboard and Mouse Combo*	X	X	X

*Keyboard contains 25% post-consumer recycled plastic material

Mice	DM	MT	SFF
HP PS/2 Mouse		X	X
HP USB Mouse	X	X	X
HP USB 1000dpi Laser Mouse	X	X	X
HP USB and PS/2 Washable Mouse	X	X	X

Power-on from Keyboard Feature

The HP ProDesk 400 G1 Desktop Mini Business PC includes a feature allowing for powering on the PC from the keyboard.

Hardware setup for power-on from keyboard

The keyboard must be connected to a specific USB port on the system. This USB port can be found on the back of the unit and is indicated by a small keyboard icon.

System setup for power-on from keyboard:

Power-on from keyboard must be enabled in the system BIOS. The default factory state is OFF. To enable the feature in the system BIOS, perform the following steps:

1. Power on the PC while holding down the F10 button to enter the Setup Utility (note: use arrow keys and Enter/Tab keys to navigate the Setup Utility)
2. From the “Power” menu choose “Hardware Power Management”. Press “Enter”
3. From the Hardware Power Management Menu scroll to “Power on from USB Kbd Port” and choose “Enable”
4. Choose F10 to Accept
5. From the “File” menu choose “Save Changes and Exit”. The system will then boot up with the feature enabled.

Your system is now setup to power-on from the keyboard. To turn the power on simply press any key.

HP BIOS

Key features of the HP BIOS include:

- UEFI specification 2.3.1
- Absolute Persistence Agent – To ensure tracking and tracing services remains active, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Business Desktop computer in any enterprise environment.
- Acoustic performance – Industry leading acoustic emissions across the range of operating conditions.
- Serviceability – HP BIOS provides diagnostic and detailed service information.

Standard Features and Configurable Components

- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Business Desktop computers, including BIOS updates from within DOS (DOSFlash), BIOS updates from within Windows (HPQFlash), HP Client Manager, and fail-safe recovery. In addition, the BIOS has the capability to replicate settings across all like systems in the Enterprise using the Replicated Setup option in BIOS Setup, or using tools available from the HP support website in the Business Desktop BIOS Utilities and BIOS Configuration Utility packages.
- HP BIOS uses PKI signing of the BIOS for trusted BIOS upgrades and recovery.

Additional HP BIOS features:

- Power-On password – Helps prevent an unauthorized user from powering on the system.
- Administrator password – Also known as the setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS version cannot be changed and changes cannot be made to BIOS settings using F10 setup or under the OS.
- Advanced Configuration and Power Interface (ACPI) – Represents a significant innovation in power and configuration management, allowing operating systems and applications to manage power based on activity and usage.
- S5 Max Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 1W is S5 (when turned off). When S5 Max Power Savings feature is enabled power to slots is turned off along with WOL functionality.

MANAGEABILITY

Fully manageable and supported by industry-standard HP Client Management Solutions. Optional LANDesk management tools simplify mobile device management and security. Simplify everything from deployment or migration to daily management, security, licensing, and more—and stop downtime before it starts.

- Hardware Management: Inventory, Device config and BIOS updates, HW alerting, Driver updates
- Software Management: Deployment, App Management, Patch Management; Deployment and Migration; Proactive HW and SW Management; Mobile Users and Device Management; Remote Assistance / Help Desk
- LANDesk Management Suite 9.5 (LDMS) – optional – contact HP representative for part numbers
- Hardware integration with Microsoft System Center Configuration Manager: Client Integration Kit (CIK), Client Catalog, Client Driver Packs
- HP SoftPaq Download Manager (SDM)
- HP System Software Manager (SSM)
- HP BIOS Configuration Utility (BCU)
- HP Driver Packs
- HP Client Management Interface (HP CMI)
- Absolute Persistent Software.

SECURITY	DM	MT	SFF
Trusted Platform Module (TPM) 1.2	X	N/A	N/A
SATA port disablement (via BIOS)	X	X	X
DriveLock	X	N/A	N/A
Serial, parallel, USB enable/disable (via BIOS)	X	X	X
Optional USB Port Disable at factory (user configurable via BIOS)	X	X	X
Removable media write/boot control	X	X	X
Power-On password (via BIOS)	X	X	X
Administrator password (via BIOS)	X	X	X
HP Chassis (1 bay) Security Kit	N/A	X	N/A

Standard Features and Configurable Components

Support for chassis padlocks and cable lock devices	X	X	X
Dual VESA Mount	X		
Security Sleeve	X		

ENVIRONMENTAL & REGULATORY

ENERGY STAR® certified models available

EPEAT® registered where applicable/supported. EPEAT registration varies by country. See www.epeat.net for registration status by country.

Low halogen (chassis, all internal components and modules) (External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.)

TAA compliant models available.

PORTS

I/O Ports – Standard

	DM	MT	SFF
USB 2.0	2 (rear);	2 (front); 4 (rear); 1(internal)	2 (front); 4 (rear); 1(internal)
USB 3.0	2 (front); 2 (rear)	2 (front)	2 (front)
Serial (RS-232)	N/A	1	1
PS/2	N/A	1 keyboard (purple) 1 mouse (green)	1 keyboard (purple) 1 mouse (green)
Video	1 VGA 1 DisplayPort	1 VGA 1 DVI-D	1 VGA 1 DVI-D

NOTE: When configured with an Intel® Celeron, Pentium or 4th generation Intel® Core i3 CPU only two of the available video output ports are active.

Audio	Front: Headphone/mic	Front: Headphone/mic Rear: Line in/out 3.5mm diameter	Front: Headphone/mic Rear: Line in/out 3.5mm diameter
RJ-45 Network Interface	1	1	1

BAYS

	DM	MT	SFF
3.5" external storage drive		1	1
5.25" ODD		1	N/A
Slim ODD		N/A	1
2.5” internal storage drive	1	N/A	1
3.5” internal storage drive		2	1
Internal M.2 connector for optional wireless NIC	1		
Internal M.2 connector for optional SSD drive	1		

SERVICE AND SUPPORT*

On-site Warranty [1]: One-year (1-1-1) limited warranty delivers one year of on-site, next business day [2] service for parts and labor and includes free telephone support [3] 24 x 7. One-year onsite and labor are not available in all countries. Service offers terms up to 5 years by choosing an optional HP Care Pack. To choose the right level of service for your HP product, visit HP

Standard Features and Configurable Components

Care Pack Central: www.hp.com/go/cpc

*3/3/3 Warranty available in North America

NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply. Other warranty variations may be offered in your region.

NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

NOTE 3: Technical telephone support applies only to HP-configured and third-party HP qualified hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

Technical Specifications – Operating Systems and Software

OPERATING SYSTEMS

Preinstalled

Windows 8.1 Pro (64-bit)*
Windows 8.1 (64-bit)*
Windows 8.1 Pro for Education (64-bit)*
Windows 7 Professional (32-bit)*
Windows 7 Professional (64-bit)*
Windows 7 Professional (32-bit) (available through downgrade rights from Windows 8.1 Pro)**
Windows 7 Professional (64-bit) (available through downgrade rights from Windows 8.1 Pro)**
FreeDOS 2.0
Novell SUSE Linux® Enterprise Desktop 11

For all Preinstalled operating systems HP provides Microsoft WHQL certified (where applicable) drivers on www.hp.com at the time of product announcement.

Web Support Windows 7 Enterprise (32-bit or 64-bit)

For all Supported operating systems HP performs testing of the OS, and makes available all HP value add software (OS dependent). Certified drivers are made available on www.hp.com within 30 days of product announcement.

Certified

Novell SUSE Linux Enterprise Desktop 11[1]
Red Hat Enterprise Linux 64[1]

For all Certified operating systems HP will submit hardware to the operating system vendor for testing and certification. All drivers would be obtained from the operating system vendor, not supplied by HP. Certification will be posted by the operating system vendor.

*Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows functionality. See http://www.microsoft.com.

**This system is preinstalled with Windows® 7 Professional software and also comes with a license and media for Windows 8.1 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

1The following features are not supported by Novell SUSE Linux Enterprise Desktop:

- Intel® Gigabit CT Desktop NIC
- Broadcom NetXtreme Gigabit Ethernet Plus
- HP Media Card Reader
- HP Client Security
- HP Blu-ray Writer playback of commercial movies
- HP 2nd serial port adapter
- Power Management features

Systems configured with Linux do not qualify for ENERGY STAR®

The following features are not supported by Red Hat Enterprise Linux 64:

- TPM v1.2 embedded Security Chip
- Intel® Gigabit CT Desktop NIC
- HP Wireless 802.11b/g/n NIC
- HP Media Card Reader
- HP Blu-ray Writer
- HP 2nd serial port Adapter

- HP USB Smart Card (CCID) Keyboard
- Power Management features

Systems configured with Linux do not qualify for ENERGY STAR®

SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS

Included	Windows 7	Windows 8.1
Security	HP Client Security[1] HP Drive Encryption (FIPS 140-2)[2] HP Device Access Manager with Just In Time Authentication HP Password Manager HP File Sanitizer (SSDs and Hybrid Drives not supported)[3] HP Disk Sanitizer External Edition[4] Microsoft Security Essentials[5]	Disk Sanitizer External Edition[1] Microsoft Defender
MultiMedia	Cyberlink Power DVD, BD Cyberlink Power2Go (Secure Burn)	Cyberlink Power DVD, BD Cyberlink Power2Go (Secure Burn)
Communication		HP Wireless Hotspot
HP Value Add	HP ePrint Driver[6] HP PageLift HP Support Assistant HP Recovery Disk Creator	HP ePrint Driver[2] HP PageLift HP Recovery Manager HP Support Assistant
3rd Party	Adobe Flash Player Box Skype	Skype
Microsoft Products	Buy Office	Buy Office

1. HP Client Security requires Windows.
2. HP Drive Encryption requires Windows. Data is protected prior to Drive Encryption login. Turning the PC off or into hibernate logs out of Drive Encryption and prevents data access.
3. For the use cases outlined in the DOD 5220.22-M Supplement. Does not support Solid State Drives (SSDs). Initial setup required. Web history deleted only in Internet Explorer and Firefox browsers and must be user enabled. With Windows 8.1, user must turn off Enhanced Protection Mode in IE11 for shred on browser close feature.
4. Available via download. HP Disk Sanitizer External Edition is for the use cases outlined in the DOD 5220.22-M Supplement. Does not support Solid State Drives (SSDs). Requires Disk Sanitizer, External Edition for Business Desktops from hp.com. Requires Windows.
5. Available on Windows 7 only.
6. Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hp.com/go/eprintcenter).Requires optional broadband module. Broadband use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary.

Technical Specifications - Graphics

Intel® HD Graphics		
VGA Controller	Integrated	
DisplayPort	Multimode capable; supports HDCP, Display Port Audio (2 streams), HBR2 link rates and Multi-Stream Technology for a maximum of 2 displays (including the integrated panel)	
Bus Type	N/A	
RAMDAC	N/A	
Memory	Intel® graphics do not have dedicated memory but utilizes some of the computer's system memory The amount of memory used for graphics depending on the amount of system memory installed, BIOS settings, operating system, and system load. 32 MB is pre-allocated for graphics use at system boot time. Additional memory can be allocated at boot time by the BIOS for PAVP (Protected Audio Video Playback) support for playback of protected video content. Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.	
Maximum Graphics Memory	Microsoft Windows 7	Windows 8.1
	Up to 1.7GB	Up to 1.8GB
	Note: the actual amount of maximum graphics memory can be less than the amounts listed above depending upon your computer's configuration.	
Maximum Color Depth	32 bits/pixel	

Graphics/Video API Support	4th Generation Intel® Core™ processors:
	• The Processor Graphics contains a refresh of the seventh generation graphics core enabling substantial gains in performance and lower power consumption. Up to 16 EU support.
	• Next Generation Intel® Clear Video Technology HD Support is a collection of video playback and enhancement features that improve the end user's viewing experience
	  ○ Encode/transcode HD content
	  ○ Playback of high definition content including Blu-ray Disc
	  ○ Superior image quality with sharper, more colorful images
	• DirectX Video Acceleration (DXVA) support for accelerating video processing
	  ○ Full AVC/VC1/MPEG2 HW Decode
	• Advanced Scheduler 2.0, 1.0
	• Windows 7, Windows 8.1, Linux OS Support
	• DirectX 11.1
	• OpenGL 4.0
	• Open CL 1.2	

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rates
800x600	60 Hz
1024x768	60 Hz
1152x864	60 Hz
1280x600	60 Hz

Technical Specifications - Graphics

1280x720	60 Hz
1280x800	60 Hz
1280x960	60 Hz
1280x1024	60 Hz
1360x768	60 Hz
1366x768	60 Hz
1400x1050	60 Hz
1440x900	60 Hz
1600x900	60 Hz
1600x1200	60 Hz
1680x1050	60 Hz
1920x1080	60 Hz
1920x1200	60 Hz

AMD Radeon™ HD 8470 Graphics Card

Form Factor	Full Height
Graphics Controller	AMD Radeon HD 8470
Core Clock	775MHz
Memory Clock	900MHz
Memory	2GB, DDR3, 64-bit wide
Bus Type	PCIe Gen2
Max. Power	< 30W
Power Source Support	12V and 3.3V
3D API Support	DX11
HDCP Support	Yes
Display Max. Resolution	Digital 2560 x 1600 Analog 2048 x 1536
Supported Graphics APIs	DX11, OpenGL, full 1080p BD (H264) playback in hardware, HDMI 1.4 support

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rates
800 x 600	60 Hz
1024 x 768	60 Hz
1280 x 720	60 Hz

Technical Specifications - Graphics

1280 x 768	60 Hz
1280 x 1024	60 Hz
1360 x 768	60 Hz
1440 x 900	60 Hz
1600 x 900	60 Hz
1680 x 1050	60 Hz
1920 x 1080	60 Hz

NVIDIA® NVS™ 310 Graphics Card

Introduction	The NVIDIA® NVS™ 310 Graphics Card is a PCI Express low profile form factor graphics add-in card targeted as an active low cost graphics solution for the corporate business and enterprise markets. The NVIDIA® NVS™ 310 graphics card is an ideal solution for customers requiring a small form factor graphics add-in card for either standard or small form factor PC designs.	
Performance and Features	The NVIDIA® NVS™ 310 Graphics Card offers 512 MB of ultrafast DDR3 memory and is capable of supporting up to 2 displays. DisplayPort connector supports multimode technology to support connection to DVI-D, VGA and HDMI monitors with optional adapters in kits NR078AA, FH973AT, BP937AA, AS615AA. For a DisplayPort to DisplayPort connections use the optional DisplayPort Cable Kit VN567AA.	
Form Factor	Low Profile: 2.713 × 6.15 in	
Graphics Controller	NVIDIA® NVS™ 310	
Memory Clock	875MHz	
Memory Size	512 MB DDR3	
Memory Bandwidth	14 GB/s	
Max. Power	19.5W	
Display Max. Resolution	Up to 2560 x 1600 (digital display) per display	
Display Output	Up to 2 displays in the following configurations	
	DisplayPort output:	• Drives two DisplayPort enabled digital display at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking, when connected natively using the 2 DisplayPort connectors on the NVS 310 graphics card • Supports 2 monitors up to resolution of 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort Multi-Stream topology technology.

Technical Specifications - Graphics

	DVI-D output:	• Drives two digital display at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors • Drives two digital display at resolutions up to 2560× 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors
	HDMI output:	• NVS 310 is capable of driving two high definition (HD) panels up to resolutions of 1920 × 1080P at 60 Hz using DisplayPort to HDMI cable adaptors
	VGA display output:	• Drives two analog display at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	**Maximum Refresh Rates (Hz) by Connection**			
	DisplayPort to VGA	DisplayPort to DVI-D	DisplayPort to HDMI	DisplayPort
640 x 480	85	60	60	60
800 x 600	85	60	60	60
1024 x 768	85	60	60	60
1280 x 720	85	60	60	60
1280 x 1024	85	60	60	60
1440 x 900	75	60	60	60
1600 x 1200	60	60	60	60
1680 x 1050	60	60	60	60
1920 x 1080	60-R	60-R	60	60
1920 x 1200	60-R	60-R		60
1920 x 1440				60
2048 x 1536				60
2560 x 1600				60

NVIDIA® NVS™ 315 1GB PCIe x 16 Graphics Card	
Introduction	Get efficient dual-display graphics performance in a PCI Express low-profile graphics card with the NVIDIA® NVS™ 315 PCIe x16 1 GB Graphics Card, an ideal desktop graphics solution for professional business and commercial applications.
Performance and Features	The NVIDIA® NVS™ 315 Graphics Card offers 1 GB of ultrafast DDR3 memory and is capable of supporting up to 2 displays. DisplayPort connector supports multimode technology to support connection to DVI-D, VGA and HDMI monitors with optional adapters in kits NR078AA, FH973AT, BP937AA, AS615AA. For a DisplayPort to DisplayPort connections use the optional DisplayPort Cable Kit VN567AA.
Form Factor	Low Profile: 2.713 × 6.15 in

Technical Specifications - Graphics

Graphics Controller	NVIDIA® NVS™ 315
Memory Clock	875MHz
Memory Size	512 MB DDR3
Memory Bandwidth	14 GB/s
Connectors	DMS-59 , with support for dual VGA, dual DVI or dual Display Port with the appropriate adapter cable
Display Max. Resolution	Up to 2048 x 1536 VGA; 1920 x 1200 DVI; 2560 x 1600 DisplayPort
Display Output	Up to 2 displays in the following configurations

	• Dual DVI :
	  ○ Drives two DVI displays using optional HP DMS59 DVI Dual-head Connector Cable DL139A
	• Dual DisplayPort :
	  ○ Drives two DisplayPort using optional HP DMS-59 to Dual DisplayPort kit XP688AA
	• Dual VGA :
	  ○ Drives two analog using the included HP DMS-59 to Dual VGA Cable

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	**Maximum Refresh Rates (Hz) by Connection**	
	Analog Connection	Digital Connection
640 x 480	85	60
720 x 480	85	60
720 x 576	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 768	85	60
1280 x 1024	85	60
1440 x 900	75	60
1600 x 1024	85	60
1600 x 1200	85	60
1680 x 1050	75	60
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	N/A
2048 x 1536	75	N/A
2560 x 1440	N/A	60*
2560 x 1600	N/A	60*

		* Display Port Only

NVIDIA® GeForce® GT630 Graphics Card	
Introduction	The NVIDIA® GeForce® GT630 DP (2GB) PCIe x16 Card Graphics Card provides a full height, PCI Express x16 graphics add-in card solution based on the NVIDIA® Kepler™ Architecture GPU. The card is designed to support three display connections through its DVII, and two DisplayPort connectors. An ideal solution for desktop PC customers seeking enhanced 2D and advanced 3D graphics performance, the NVIDIA® GeForce® GT630 DP (2GB) PCIe x16 Cards are an excellent choice for business users who want run multiple displays from a single graphics board. Engage in Web conferencing or video or photo editing, while improving your everyday business PC experience with better graphics and excellent visual display quality.
Performance and Features	The NVIDIA® GeForce® GT630 DP (2GB) PCIe x16 Cards deliver superior PCI Express (PCIe) Gen 3 features including: • Unprecedented flexibility for new applications and enhanced performance • Support for NVIDIA surround technology • Run multiple displays from a single graphics card • Full 16 lane PCIe Generation 3 bus support with peak bandwidth support • Wireless Display ready for future support
Form Factor	PCIe x16 Card
Graphics Controller	NVIDIA® Kepler™ Architecture GPU
Core Clock	875 MHz
Memory Clock	891 MHz
Memory Size	2 GB DDR3 128 bit
Memory Bandwidth	28.5 GB/s
Display Max. Resolution	2560 x 1600 digital, 2048 x 1536 analog
Display Support	Integrated 400 MHz RAMDAC

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	**Maximum Refresh Rates (Hz)**	
	Analog Connection	Digital Connection
640 x 480	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 1024	85	60

Technical Specifications - Graphics

1440 x 900	75	60
1600 x 1200	85	60
1680 x 1050	75	60
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	60
2048 x 1536	75	60
2560 x 1600	N/A	60

AMD Radeon™ HD 8350 1GB PCIe x16 DH Graphics Card

Introduction	Get stable 2D and advanced 3D graphics performance from the AMD Radeon™ HD 8350 1 GB PCIe x16 DH Graphics Card, a low profile, PCI Express x16 graphics add-in card based on the AMD Radeon™ HD 8350 GPU, great for Web conferencing or video and photo editing.
Form Factor	PCie x16
Graphics Controller	AMD Radeon™ HD 8350
Core Clock	GPU engine operates at 523 MHz
Memory	1GB, DDR3, SDRAM
Memory Clock	875 MHz
HDCP Support	Yes
Display Max. Resolution	Digital 1920 x 1200 Analog 2048 x 1536

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

	Analog Connection	Digital Connection
640 x 480	85	60
720 x 480	85	60
720 x 576	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 768	85	60
1280 x 1024	85	60
1440 x 900	75	75
1600 x 1024	85	60
1600 x 1200	85	60
1680 x 1050	75	75-R

Technical Specifications - Graphics

1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	N/A
2048 x 1536	75	N/A
2560 x 1440	N/A	N/A
2560 x 1600	N/A	N/A

AMD Radeon™ HD 8490 1GB PCIe x16 Graphics Card

Introduction	Get impressive graphics and high resolution dual-display performance in a low profile, PCI Express x16 graphics add-in card based on the AMD Radeon™ HD 8490 Graphics Processor. Improve your everyday PC, Web conferencing, and video or photo editing.
Form Factor	PCie x16
Graphics Controller	AMD Radeon™ HD 8490
Core Clock	GPU engine operates at 875 MHz
Memory	1GB, DDR3, SDRAM
Memory Clock	900 MHz
HDCP Support	Yes
Display Max. Resolution	Digital 2560 x 1600 Analog 2048 x 1536

Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

	Analog Connection	Digital Connection
300 x 200	85	60
320 x 240	85	60
400 x 300	85	60
640 x 480	85	60
720 x 480	85	60
720 x 576	85	60
800 x 600	85	60
1024 x 768	85	60
1280 x 720	85	60
1280 x 768	85	60
1280 x 1024	85	60
1440 x 900	75	75
1600 x 900	85	60

Technical Specifications - Graphics

1600 x 1024	85	60
1600 x 1200	85	60
1680 x 1050	75	75-R
1920 x 1080	85	60-R
1920 x 1200	85	60-R
1920 x 1440	85	N/A
2048 x 1536	75	N/A
2560 x 1440	N/A	60
2560 x 1600	N/A	60

Technical Specifications – Hard Disk and Solid State Storage

Introduction:

HP Serial Advanced Technology Attachment (SATA) Hard Drives maximize the performance of HP Business PCs by providing the technologies to meet your increasing storage demands with high-capacity drives offering superior reliability and performance.

SATA provides faster data transfer speeds, better system cooling airflow, more bandwidth, more headroom for speed increases in future generations and better data integrity. A next-generation technology, the SATA interface connects hard drives to the PC platform enabling easy aggregation of multiple hard drives into a single PC. This offers you the additional benefits of dedicated bandwidth, the ability to more easily identify device failures and scalability. The HP ProDesk 400 G1 Series Business PC supports the latest SATA 6.0Gb/s specification.

SMART IV Technology

Self Monitoring Analysis and Reporting Technology (SMART) hard drive technology allows hard drives to monitor their own health and to raise flags if imminent failures are predicted. If the drive determines that a failure is imminent, the SMART hard drive technology enables the intelligent manageability or management software to generate a fault alert. While the current versions of SMART hard drives do a good job monitoring the data on the hard drive media, the ever increasing emphasis on reliability and quality has promoted HP to implement SMART IV technology which constantly checks that the data flow from host interface to media and media to host interface is not compromised. This is accomplished by inserting a 2 byte parity code into every 512 byte block in the data path of the hard drive's Cache RAM. This unique parity checking performed by HP's SMART IV technology hard drives, allows for more complete error detection coverage encompassing the entire data path between the host and the hard drive.

Smart IV is also known as IOEDC: I/O Error Detection Code.

Native Command Queuing

NCQ or Native Command Queuing is a SATA protocol extension that allows the hard drive to have several write or read commands outstanding at the same time. In contrast, normal non-queued operation requires each command to be completed before the next command is issued by the host system. Queuing allows the drive to complete the commands in the order that allows for best overall throughput. It also involves an advanced method of transferring data to or from the host, called First Party Direct Memory Access (FPDMA), which allows the hard drive and the host controller to manage the data transfers for multiple outstanding commands, without involving the host processor. NCQ can contribute to better performance but the results are dependent on many factors, including the access patterns of the various applications and operating system functions that are initiating drive accesses. Enabling NCQ features in the hard drive requires AHCI support from the host system BIOS, controller, and driver. AHCI support is typically implemented in RAID configurations.

Note: GB = 1 billion bytes. Actual available capacity is less.

HP 500-GB 7.2K SATA 6.0Gb/s 2.5” Hard Disk Drive	
Capacity	500,107,862,016 bytes
Rotational Speed	7,200 rpm
Interface	Serial ATA 2.0 (6.0 Gb/s)
Buffer Size	16 MB

Technical Specifications – Hard Disk and Solid State Storage

Logical Blocks	976,773,168	
Seek Time (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	12 ms
	Full-Stroke:	25 ms
Height (nominal)	0.374 in/9.5 mm	
Width (nominal)	Media diameter: 2.5 in/63.5 mm	
	Physical size: 2.75 in/70 mm	
Operating Temperature	41° to 131° F (5° to 55° C)	

HP 1-TB SATA 6G 2.5" 8GB Solid State Hybrid Drive (SSHD)		
Formatted Capacity	1 TB	
Spindle Speed	5,400 rpm +/- 0.2%	
Drive Type	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
Interface	Serial ATA (SATA)	
Cache Buffer	64 MB	
NAND Flash Commercial Multilevel Cell (cMLC)	8 GB	
Number of Sectors	976,773,168	
Seek Time (typical reads)	Single Track:	2.0 ms
	Average:	12 ms
Height	0.374 +/-.008 in (9.5 +/- 0.2 mm)	
Width	2.750 +/- 0.010 in (69.85 +/- 0.25 mm)	
Length	3.951 +0.008 / -0.010 in (100.35 +0.20 / -0.25 mm)	
Weight	0.254 lb/115 g (max)	
Operating Temperature	32° to 140° F (0° to 60° C)	

Technical Specifications – Hard Disk and Solid State Storage

HP 500 GB SATA 6G 2.5" 8GB Solid State Hybrid Drive (SSHD)		
Formatted Capacity	500 GB	
Spindle Speed	5,400 rpm +/- 0.2%	
Drive Type	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
Interface	Serial ATA (SATA)	
Cache Buffer	64 MB	
NAND Flash Commercial Multilevel Cell (cMLC)	8 GB	
Number of Sectors	976,773,168	
Seek Time (typical reads)	Single Track:	2.0 ms
	Average:	12 ms
Height	0.268 +/-.008 in (6.8 +/- 0.2 mm)	
Width	2.750 +/- 0.010 in (69.85 +/- 0.25 mm)	
Length	3.951 +0.008 / -0.010 in (100.35 +0.20 / -0.25 mm)	
Weight	0.209 lb/95 g (max)	
Operating Temperature	32° to 140° F (0° to 60° C)	

HP 500-GB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive		
Capacity	500,107,862,016 bytes	
Rotational Speed	7,200 rpm	
Interface	Serial ATA 3.0 (6.0 Gb/s)	
Buffer Size	16 MB	
Logical Blocks	976,773,168	
Seek Time (typical reads, includes controller overhead, including settling)	**Single Track:**	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms

Technical Specifications – Hard Disk and Solid State Storage

Height (nominal)	1 in/2.54 cm
Width (nominal)	Media diameter: 3.5 in/8.89 cm
	Physical size: 4 in/10.2 cm
Operating Temperature	41° to 131° F (5° to 55° C)

HP 128 GB Solid State Drive

Unformatted Capacity	128 GB*	
Architecture	Multi Level Cell (MLC) NAND	
Interface	SATA 6 GB/sec	
Dimensions (W x H x D)	2.75 x 0.276 x 3.96 in (6.985 x 0.7 x 10.05 cm)	
Weight	0.16 lb (73 g)	
Bandwidth Performance	Sustained Sequential Read:	Up to 450 MB/ss
	Sustained Sequential Write:	Up to 260 MB/s
	Random Read (4KB):	up to 46K IOPs
	Random Write (4KB):	up to 56K IOPs
Latency	Read:	55ms (TYP)
	Write:	55ms (TYP)
Power	DC power requirement:	Min 4.5 V; Max 5.5 V
	Total power consumption:	160 mW (Active) ; <85 mW; (Idle)
Useful Drive Life	1.2 million device hours**	
Environmental (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity (operating):	5% to 95%
	Shock:	1,500 G/1.0 msec
Regulations	UL, CSA, EN 60950-2000, CISPR Pub 22 Class B, CNS 13438, AS/NZS CISPR 22:2002 Class B, Korea KCC, CE Mark	

*For solid state disk drives, GB means 1 billion bytes. Actual formatted capacity is less. Up to 16GB for Windows 7 and up to 36GB for Windows 8.1 is reserved for system recovery software
** The product achieves a mean time between failure (MTBF) based on population statistics not relevant to individual units.

Technical Specifications – Hard Disk and Solid State Storage

HP 128 GB* (non-SED) TLC Solid State Drive		
Unformatted Capacity	128 GB*	
Architecture	Triple Level Cell (TLC) NAND	
Interface	SATA 6 GB/sec	
Dimensions (W x H x D)	2.75 x 0.276 x 3.96 in (6.985 x 0.7 x 10.05 cm)	
Weight	0.1 lb (45 g)	
Bandwidth Performance	Sustained Sequential Read:	Up to 510 MB/ss
	Sustained Sequential Write:	Up to 140 MB/s
	Random Read (4KB):	up to 90K IOPs
	Random Write (4KB):	up to 36K IOPs
Latency	Read:	55ms (TYP)
	Write:	55ms (TYP)
Power	DC power requirement:	Min 4.75 V; Max 5.25 V
	Total power consumption:	160 mW (Active) ; <85 mW; (Idle)
Useful Drive Life	1.2 million device hours**	
Environmental (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity (operating):	5% to 95%
	Shock:	1,500 G/1.0 msec
Regulations	UL, CSA, EN 60950-2000, CISPR Pub 22 Class B, CNS 13438, AS/NZS CISPR 22:2002 Class B, Korea KCC, CE Mark	

* For solid state disk drives, GB means 1 billion bytes. Actual formatted capacity is less. Up to 16GB for Windows 7 and up to 36GB for Windows 8.1 is reserved for system recovery software.** The product achieves a mean time between failure (MTBF) based on population statistics not relevant to individual units.

HP 256 GB* (non-SED) TLC Solid State Drive	
Unformatted Capacity	256 GB*
Architecture	Triple Level Cell (TLC) NAND
Interface	SATA 6 GB/sec
Dimensions (W x H x D)	2.75 x 0.276 x 3.96 in (6.985 x 0.7 x 10.05 cm)

Technical Specifications – Hard Disk and Solid State Storage

Weight	0.1 lb (45 g)	
Bandwidth Performance	Sustained Sequential Read:	Up to 510 MB/s
	Sustained Sequential Write:	Up to 280 MB/s
	Random Read (4KB):	up to 90K IOPs
	Random Write (4KB):	up to 70K IOPs
Latency	Read:	55ms (TYP)
	Write:	55ms (TYP)
Power	DC power requirement:	Min 4.75 V; Max 5.25 V
	Total power consumption:	160 mW (Active) ; <85 mW; (Idle)
Useful Drive Life	1.2 million device hours**	
Environmental (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity (operating):	5% to 95%
	Shock:	1,500 G/1.0 msec
Regulations	UL, CSA, EN 60950-2000, CISPR Pub 22 Class B, CNS 13438, AS/NZS CISPR 22:2002 Class B, Korea KCC, CE Mark	

* For solid state disk drives, GB means 1 billion bytes. Actual formatted capacity is less. Up to 16GB for Windows 7 and up to 36GB for Windows 8.1 is reserved for system recovery software.** The product achieves a mean time between failure (MTBF) based on population statistics not relevant to individual units.

HP 256 GB SATA 2.5” Self-Encrypting (SED) Solid State Drive

Unformatted Capacity	256,186,209,271 bytes
Architecture	Self-Encrypting (SED) Solid State Drive with 25nm MLC NAND Flash and SATA interface
Interface	Serial ATA 2.0 (3.0 Gb/s)
NAND Flash	25nm MLC NAND Flash
Height	.275 in/7mm
Width	2.75 in/69.85 mm
Length	3.95 in/100.5 mm
Weight	0.161 lb (73 g)

Technical Specifications – Hard Disk and Solid State Storage

Bandwidth Performance	Sustained Sequential 128k Read:	Up to 450 MB/s
	Sustained Sequential 128k Write:	Up to 260 MB/s
	Random 4k Read:	Up to 46K IOPs
	Random 4k Write:	Up to 56K IOPs
Latency	Read:	55 µs
	Write:	55 µs
Power	SATA power consumption:	160 mW (active average); <85 mW (idle average)
Useful Drive Life	72TB written, up to 40GB/day for 5 years	
Environmental (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/1 ms

HP 500-GB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive		
Capacity	500,107,862,016 bytes	
Rotational Speed	7,200 rpm	
Interface	Serial ATA 3.0 (6.0 Gb/s)	
Buffer Size	16 MB	
Logical Blocks	976,773,168	
Seek Time (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms
Height (nominal)	1 in/2.54 cm	
Width (nominal)	Media diameter: 3.5 in/8.89 cm	
	Physical size: 4 in/10.2 cm	
Operating Temperature	41° to 131° F (5° to 55° C)	

Technical Specifications – Hard Disk and Solid State Storage

HP 1-TB 7.2K rpm SATA 6.0Gb/s 3.5” Hard Disk Drive		
Capacity	1,000,204,886,016 bytes	
Rotational Speed	7,200 rpm	
Interface	Serial ATA 3.0 (6.0 Gb/s)	
Buffer Size	32 MB	
Logical Blocks	1,953,525,168	
Seek Time (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms
Height (nominal)	1 in/2.54 cm	
Width (nominal)	Media diameter: 3.5 in/8.89 cm	
	Physical size: 4 in/10.2 cm	
Operating Temperature	41° to 131° F (5° to 55° C)	

HP 2-TB 7.2K rpm SATA 6.0Gb/s 3.5” Hard Disk Drive		
Unformatted Capacity	2 TB	
Rotational Speed	7,200 rpm	
Interface	SATA 6Gb/s NCQ	
Cache, Multisegmented (MB)	64 MB	
Seek Time (average)	Read	<8.5 ms
	Write	<9.5 ms
Height	1.028 in/26.11 mm	
Width	4.0 in/101.6 mm	
Depth	5.787 in/146.99 mm	
Weight	1.38 lb/626 g	
Operating Temperature	41° to 131° F (5° to 55° C)	

Technical Specifications - Removable Storage

HP Slim SuperMulti DVD Writer Drive		
Height	12.7mm height	
Orientation	Either horizontal or vertical	
Interface type	SATA/ATAPI	
Disc recording capacity	Up to 8.5 GB DL or 4.7 GB standard	
Dimensions (W x H x D)	5.04 x 0.5 x 5.0 in (128 x 12.7 x 127 mm) without bezel	
Weight (max)	0.42 lb (190 g)	
Write speeds	DVD-RAM	Up to 5X
	DVD-R DL	Up to 6X
	DVD+R	Up to 8X
	DVD+RW	Up to 8X
	DVD+R DL	Up to 6X
	DVD-R	Up to 8X
	DVD-RW	Up to 6X
	CD-R	Up to 24X
	CD-RW	Up to 24X
Read speeds	DVD-RAM	Up to 5X
	DVD-RW, DVD+RW	Up to 8X
	DVD-R DL, DVD+R DL	Up to 8X
	DVD+R, DVD-R	Up to 8X
	DVD-ROM DL, DVD-ROM	Up to 8X
	CD-ROM, CD-R	Up to 24X
	CD-RW	Up to 24X
Access time (typical reads, including settling)	Random	DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical)
	Full Stroke	DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical)
	Stop Time	6 seconds (typical)
Power	Source	Slimline SATA DC power receptacle
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p
	DC Current	5 VDC (< 1000 mA typical, 1600 mA maximum)
Environmental conditions (operating - non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%

Technical Specifications - Removable Storage

	Maximum Wet Bulb Temperature	84° F (29° C)

HP Slim Blu-ray BDXL Drive			
Height	12.7mm height		
Orientation	Either horizontal or vertical		
Interface type	SATA/ATAPI		
Disc recording capacity	Up to 128 GB QL, 100 GB TL, 50 GB DL or 25 GB standard SL		
Dimensions (W x H x D)	5.04 x 0.5 x 5.0 in (128 x 12.7 x 127 mm) without bezel		
Weight (max)	Up to 0.37 lb (170 g) without bezel		
		Triple-layer	**Quadruple-layer**
Write speeds	BD-R	Up to 4X	Up to 4X
	BD-RE	Up to 2X	Not supported
		Single-layer	**Double-layer**
	BD-R	Up to 6X	Up to 6X
	BD-RE	Up to 2X	Up to 2X
	DVD-R	Up to 8X	Up to 6X
	DVD-RW	Up to 6X	Not supported
	DVD+R	Up to 8X	Up to 6X
	DVD+RW	Up to 8X	Not supported
	DVD-RAM	Up to 5X	
	CD-R	Up to 24X	
	CD-RW	Up to 24X	
		Triple-layer	**Quadruple-layer**
	BD-R	Up to 4X	Up to 4X
	BD-RE	Up to 4X	Not supported
		Single-layer	**Double-layer**
	BD-ROM	Up to 6X	Up to 6X
	BD-R	Up to 6X	Up to 6X
Read speeds	BD-RE	Up to 6X	Up to 6X
	DVD-ROM	Up to 8X	Up to 8X
	DVD-R	Up to 8X	Up to 8X
	DVD-RW	Up to 8X	
	DVD+R	Up to 8X	Up to 8X

Technical Specifications - Removable Storage

	DVD+RW	Up to 8X	
	BDMV (AACS Compliant Disc)	Up to 6X/2X (Read/Play)	
	DVD-RAM	Up to 5X	
	DVD-Video (CSS Compliant Disc)	Up to 8X/4X (Read/Play)	
	CD-R/RW/ROM	Up to24X	
	CD-DA(DAE)	Up to 20X/10X (Read/Play)	
Access time (typical reads, including settling)	Random	BD-ROM: 205 ms (typical), DVD-ROM: 185 ms (typical), CD-ROM: 165 ms (typical)	
	Full Stroke	BD-ROM: 350 ms (typical), DVD-ROM: 345 ms (typical), CD-ROM: 340 ms (typical)	
Power	Source	Slimline SATA DC power receptacle	
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p	
	DC Current	5 VDC -1200 mA typical, 2000 mA maximum	
Environmental conditions (operating - non-condensing)	Temperature	41° to 122° F (5° to 50° C)	
	Relative Humidity	10% to 80%	
	Maximum Wet Bulb Temperature	84° F (29° C)	

HP Slim DVD-ROM Drive		
Height	12.7mm	
Orientation	Either horizontal or vertical	
Interface type	SATA/ATAPI	
Dimensions (W x H x D)	5.04 x 0.5 x 5.0 in (128 x 12.7 x 127 mm) without bezel	
Weight (max)	Up to 0.37 lb (170 g) without bezel	
Read speeds	DVD+R/-R/+RW/ -RW/+R DL /-R DL	Up to 8X
	DVD-ROM	Up to 8X
	CD-ROM, CD-R	Up to 24X
	CD-RW	Up to 24X
Access time (typical reads, including settling)	Random	DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical)
	Full Stroke	DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical)
Power	Source	Slimline SATA DC power receptacle
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p
	DC Current	5 VDC - <1000 mA typical, < 1600 mA maximum

Technical Specifications - Removable Storage

Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%
	Maximum Wet Bulb Temperature (operating)	84° F (29° C)

HP Blu-ray BDXL Writer Drive			
Height	5.25-inch, half-height, tray-load		
Orientation	Either horizontal or vertical		
Interface type	SATA		
Disc capacity	Blu-ray: 128 GB QL, 100 GB TL, 50 GB DL or 25 GB standard DVD: 8.5GB DL or 4.7GB standard		
Dimensions (W x H x D)	5.8 x 1.7 x 7.1 in (14.8 x 4.2 x 18.0 cm) max		
Weight (max)	2.1 lb (950g)		
Performance	**CD-ROM Read Access time**	Random	140 ms (typical)
		Full Stroke	230 ms (typical)
	DVD-ROM Read Access time	Random	150 ms (typical)
		Full Stroke	240 ms (typical)
	BD-ROM Read Access time	Random	250 ms (typical)
		Full Stroke	350 ms (typical)
	Startup Time	(Time to drive ready from tray loading)	
		BD-ROM (SL/DL)	28S / 28S
		BD-R (SL/DL/TL/QL)	28S / 28S / 40S / 40S
		BD-RE (SL/DL/TL)	28S / 28S / 40S
		DVD-ROM (SL/DL)	18S / 18S
		DVD-R (SL/DL)	25S / 25S
		DVD-RW	25S
		DVD+R (SL/DL)	25S / 25S
		DVD+RW	25S
		DVD-RAM	35S
		CD-ROM	15S
	CD Read speeds	CD-ROM up to 40X	
		CD-R up to 40X	
		CD-RW up to 40X	

Technical Specifications - Removable Storage

	DVD Read speeds	DVD-RAM up to 5X
		DVD+/-RW up to 10X
		DVD+/-R up to 16X
		DVD+/-R DL up to 8X
		DVD-ROM up to 16X
		DVD-ROM DL up to 8X
	Blu-ray Read speeds	BD-ROM (SL/DL) up to 8X
		BD-R (SL/DL) up to 8X
		BD-R (TL/QL) up to 6X
		BD-RE (SL/DL) up to 6X
		BD-RE TL up to 4X
	CD Write speeds	CD-R up to 40X
		CD-RW up to 24X
	DVD Write speeds	DVD+/-R up to 16X
		DVD+/-R DL up to 8X
		DVD+RW up to 8X
		DVD-RW up to 6X
		DVD-RAM up to 5X
	Blu-ray Write speeds	BD-R (SL/DL) up to 6X
		BD-R (TL/QL) up to 4X
		BD-RE (SL/DL/TL) up to 2X
Power	**Source**	SATA DC power receptacle
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p
	DC Current	5 VDC -1200 mA typical, 1500 mA maximum 12 VDC -1000 mA typical, 1500 mA maximum
Environmental (all conditions non-condensing)	**Temperature** (operating)	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 90%
	Maximum Wet Bulb Temperature	86° F (30° C)

HP SuperMulti DVD Writer Drive	
Height	5.25-inch, half-height, tray-load
Orientation	Either horizontal or vertical
Interface type	SATA
Dimensions (W x H x D)	5.8 x 1.7 x 6.9 in (14.8 x 4.2 x 17.5 cm) max

Technical Specifications - Removable Storage

Weight (max)	2.1 lb (950g)		
Performance	CD-ROM Read Access	Random	120 ms typical
		Full Stroke	200 ms typical
	DVD-ROM Read Access	Random	130 ms typical
		Full Stroke	240 ms typical
	CD Media Read Transfer	CD-ROM, CD-R Read	Up to 6000 KB/s (40X)
		CD-RW Read	Up to 4800 KB/s (32X)
		Digital/Analog Audio Playback	Up to 2400 KB/s (16X)
		Digital Audio Extraction (CD-ROM, CD-R)	Up to 6000 KB/s (40X)
		Digital Audio Extraction (CD-RW)	Up to 4800 KB/s (32X)
		Video CD Playback	Up to 2400 KB/s (16X)
	DVD Media Read Transfer	DVD-ROM SL Read	Up to 21600 KB/s (16X)
		DVD-ROM DL Read	Up to 10800 KB/s (8X)
		DVD Video Playback	Up to 10800 KB/s (8X)
		DVD Video SL (other than playback)	Up to 21600 KB/s (16X)
		DVD Video DL (other than playback)	Up to 10800 KB/s (8X)
		DVD+/-R	Up to 21600 KB/s (16X)
		DVD+/-R DL	Up to 10800 KB/s (8X)
		DVD+/-RW	Up to 10800 KB/s (8X)
		DVD-RAM	Up to 6750 KB/s (5X)
	CD Media Write Transfer	CD-R	Up to 6000 KB/s (40X)
		CD-RW	Up to 600 KB/s (4X)
		CD-RW (High speed)	Up to 1500 KB/s (10X)
		CD-RW (Ultra speed)	Up to 3600 KB/s (24X)
	DVD Media Write Transfer	DVD+/-R	Up to 21600 KB/s (16X)
		DVD+/-R DL	Up to 10800 KB/s (8X)
		DVD+RW	Up to 10800 KB/s (8X)
		DVD-RW	Up to 8100 KB/s (6X)
		DVD-RAM	Up to 6750 KB/s (5X)
Media Compatibility	**Media**	**Read**	**Write**
	CD-ROM	Yes	No
	CD-R	Yes	Yes
	CD-RW	Yes	Yes
	DVD-ROM	Yes	No
	DVD-ROM DL	Yes	No
	DVD-RAM	Yes	Yes
	DVD+/-R	Yes	Yes
	DVD+/-R DL	Yes	Yes
	DVD+/-RW	Yes	Yes
Power Supply	Source	SATA DC power receptacle	

Technical Specifications - Removable Storage

	DC Power Requirement	5 VDC ± 5%	100 mV ripple p-p
		12 VDC ± 5%	200 mV ripple p-p
	DC Current	5 VDC	1000 mA (typical) 1600 mA (max.)
		12 VDC	1200 mA (typical) 2000 mA (max.)
		Total Drive Power (Standby Mode)	< 2.5W
Rear Panel	SATA Power Connector, 15-pin SATA Data Connector, 7-pin Markings to identify each connector		
Environmental conditions (all conditions non-condensing)	Operating Temperature	41° to 122° F (5° to 50° C)	
	Storage Temperature	–22° F to 140° F (–30° C to 60° C)	
	Relative Humidity	10% to 90%	
	Maximum Wet Bulb Temperature	86° F (30° C)	

HP DVD-ROM Drive			
Height	5.25-inch, half-height, tray-load		
Orientation	Either horizontal or vertical		
Interface type	SATA		
Dimensions (W x H x D)	5.8 x 1.7 x 6.9 in (14.8 x 4.2 x 17.5 cm) max		
Weight (max)	2.1 lb (950 kg)		
Performance	CD-ROM Read Access	Random	120 ms typical
		Full Stroke	200 ms typical
	DVD-ROM Read Access	Random	130 ms typical
		Full Stroke	240 ms typical
	CD Media Read Transfer	CD-ROM, CD-R Read	Up to 6000 KB/s (40X)
		CD-RW Read	Up to 4800 KB/s (32X)
		Digital/Analog Audio Playback	Up to 2400 KB/s (16X)
		Digital Audio Extraction (CD-ROM, CD-R)	Up to 6000 KB/s (40X)
		Digital Audio Extraction (CD-RW)	Up to 4800 KB/s (32X)
		Video CD Playback	Up to 2400 KB/s (16X)
	DVD Media Read Transfer	DVD-ROM SL Read	Up to 21600 KB/s (16X)
		DVD-ROM DL Read	Up to 10800 KB/s (8X)
		DVD Video Playback	Up to 10800 KB/s (8X)
		DVD Video SL (other than playback)	Up to 21600 KB/s (16X)
		DVD Video DL (other than playback)	Up to 10800 KB/s (8X)
		DVD+/-R	Up to 21600 KB/s (16X)
		DVD+/-R DL	Up to 10800 KB/s (8X)
		DVD+/-RW	Up to 10800 KB/s (8X)

Technical Specifications - Removable Storage

		DVD-RAM	Up to 6750 KB/s (5X)
Media Compatibility	**Media**	**Read**	**Write**
	CD-ROM	Yes	No
	CD-R	Yes	No
	CD-RW	Yes	No
	DVD-ROM	Yes	No
	DVD-ROM DL	Yes	No
	DVD-RAM	Yes	No
	DVD+/-R	Yes	No
	DVD+/-R DL	Yes	No
	DVD+/-RW	Yes	No
Power Supply	Source	SATA DC power receptacle	
	DC Power Requirement	5 VDC ± 5%	100 mV ripple p-p
		12 VDC ± 5%	200 mV ripple p-p
	DC Current	5 VDC	1000 mA (typical) 1600 mA (max.)
		12 VDC	1200 mA (typical) 2000 mA (max.)
		Total Drive Power (Standby Mode)	< 2.5W
Rear Panel	SATA Power Connector, 15-pin SATA Data Connector, 7-pin Markings to identify each connector		
Environmental conditions (all conditions non-condensing)	Operating Temperature	41° to 122° F (5° to 50° C)	
	Storage Temperature	–22° F to 140° F (–30° C to 60° C)	
	Relative Humidity	10% to 90%	
	Maximum Wet Bulb Temperature	86° F (30° C)	

Technical Specifications – Memory

System Memory Support

The HP ProDesk 400 G1 Business PC supports the 4th generation Intel® Core™ processor family. Based on a new PC micro-architecture, the processor is designed for a two-chip platform consisting of a processor and Platform Controller Hub (PCH). Unlike previous generations, the 4th generation Intel® Core™ processor includes an Integrated Memory Controller (IMC). The IMC supports DDR3/DDR3L protocols with two independent, 64-bit wide channels each accessing one or two DIMMs or SODIMMs.

- Two channels of non-ECC DDR3/DDR3L unbuffered dual in-line memory modules (UDIMM) or DDR3/DDR3L unbuffered small outline dual in-line memory modules (SO-DIMM) with a maximum of two DIMMs per channel
- Single-channel and dual-channel memory organization modes
- Data burst length of eight for all memory organization modes
- Memory data transfer rates of up to 1600 MT/s; actual supported data transfer rate determined by the configured processor.
- 64-bit wide channels
- DDR3/DDR3L system memory I/O voltage of 1.5V
- Theoretical maximum memory bandwidth of:
    - 21.3 GB/s in dual-channel mode assuming 1333 MT/s
    - 25.6 GB/s in dual-channel mode assuming 1600 MT/s

Platform Memory Support

- The Small Form Factor (SFF) and Microtower (MT) platforms support up to two (2) industry-standard DDR3-SDRAM DIMMs.

- The Desktop Mini (DM) platform supports up to two (2) industry-standard DDR3-SDRAM SODIMMs.

CAUTION: You must shut down the computer and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the computer is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

NOTE: For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements.

Addressing memory above 4 GB requires a 64-bit operating system.

Technical Specifications – Networking/Communication

Intel® I217LM GbE Network Connection (integrated on Desktop Mini)		
Connector	RJ-45	
System Interface	Integrated on PCA	
Controller	Intel I217LM GbE platform LAN connect networking controller	
Memory	24 KB FIFO packet buffer memory	
Data rates supported	10/100/1000 Mbps	
IEEE Compliance	802.1P 802.1Q 802.2 802.3 802.3ab 802.3az 802.3u	
Bus architecture	PCI Express and SMBus	
Data transfer mode	PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)	
Power requirement	Requires 3.3V and 0.9V or just 3.3V with integrated regulators Power consumption 0.733 Watts	
Boot ROM support	Yes	
Network transfer mode	Full-duplex	
	Half-duplex (not supported for the 1000BASE-T transceiver)	
Network transfer rate	10BASE-T (half-duplex) 10 Mbps	
	10BASE-T (full-duplex) 20 Mbps	
	100BASE-TX (half-duplex) 100 Mbps	
	100BASE-TX (full-duplex) 200 Mbps	
	1000BASE-T (full-duplex) 2000 Mbps	
Environmental	Operating Temperature:	0° to 85° C
	Operating Humidity:	60**%** RH
Management	WOL, auto MDI crossover, PXE, Muti-port teaming, RSS, Advanced cable diagnostic	
Alerting	ASF 2.0 support; AMT 9.0 support	

Technical Specifications – Networking/Communication

Realtek RTL8151GH-CG GbE LOM Network Adapter (integrated on Small Form Factor and Microtower)		
Connector	RJ-45	
System Interface	Integrated on PCA	
Controller	Realtek RTL8151GH-CG Gigabit Ethernet Controller	
Memory	16 KB FIFO packet buffer memory	
Data rates supported	10/100/1000 Mbps	
IEEE Compliance	802.1P 802.1Q 802.3 802.3ab 802.3az 802.3u	
Bus architecture	PCI Express	
Data transfer mode	PCIe-based interface for active state operation (S0 state)	
Power requirement	Requires 3.3V and 1V or just 3.3V with integrated regulators Power consumption 0.425 W	
Network transfer mode	Full-duplex	
	Half-duplex (not supported for the 1000BASE-T transceiver)	
Network transfer rate	10BASE-T (half-duplex) 10 Mbps	
	10BASE-T (full-duplex) 20 Mbps	
	100BASE-TX (half-duplex) 100 Mbps	
	100BASE-TX (full-duplex) 200 Mbps	
	1000BASE-T (full-duplex) 2000 Mbps	
Environmental	Operating Temperature:	32° to 158° F (0° to 70° C)
	Operating Humidity:	60% RH
Management	WOL, auto MDI crossover, PXE, Muti-port teaming, Advanced cable diagnostic	

Intel® Ethernet I210-T1 Gigabit Network Adapter	
Connector	RJ-45
System Interface	PCI Express x1

Technical Specifications – Networking/Communication

Controller	Intel® I210 Gigabit Ethernet Controller	
Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers	
Data rates supported	10/100/1000 Mbps	
IEEE Compliance	802.1P 802.1Q 802.2 802.3 802.3AB 802.3u 802.3x flow control	
Bus architecture	PCI-E 2.1	
Data path width	X1, 250 MB/s, Bi-directional interface	
Data transfer mode	Bus-master DMA	
Hardware certifications	FCC, B, CE, TUV-c, TUVus Mark Canada and United States, TUV-GS Mark for European Union	
Power requirement	Aux 3.3 V, 3.0 Watts in 1000 base-T and 1.0 Watts in 100 Base-T	
Boot ROM support	Yes 10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps	
Network transfer rate	10BASE-T (half-duplex) 10 Mbps	
	10BASE-T (full-duplex) 20 Mbps	
	100BASE-TX (half-duplex) 100 Mbps	
	100BASE-TX (full-duplex) 200 Mbps	
	1000BASE-T (full-duplex) 2000 Mbps (actual rate limited by PCI bus)	
Environmental	Operating Temperature:	32° to 132° F (0° to 55° C)
	Operating Humidity:	85% at 131° F (55° C)
Management	WOL, PXE, DMI, WFM 2.0	

Intel® Dual Band Wireless-N 7260 802.11 a/b/g/n (2x2) Wireless Network Interface Connection

Wireless LAN Standards	IEEE 802.11a/b/g/n
Interoperability	Wi-Fi certified (802.11 a/b/g/n WMM, WPA, WPA2 and WPS)

Technical Specifications – Networking/Communication

	Cisco Compatible Extensions Program compliant with Microsoft Windows 7, Windows Vista and XP.	
	NOTE: WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.	
Frequency Band	802.11b/g/n	2.402-2.482 GHz
	802.11a/n	4.9 - 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz
Antenna Structure	2 transmit; 2 receive (2x2)	
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)	
Modulation	Direct Sequence Spread Spectrum CCK, BPSK, QPSK, 16-QAM, 64-QAM	
Security	• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI	
	Note: Check latest software/driver release for updates on supported security features.	
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.	
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between band Access Points	
Output Power	• 2.4G: +13.5dBm minimum • 5G: +12dBm minimum	
	Note: Maximum output power may vary by country according to local regulations.	
Power Consumption	Transmit: 2.0 Watts	
	Receive: 1.6 Watts	
	Idle mode: 250 mW (WLAN associated) In Power Save Polling mode and on battery power.	

Technical Specifications – Networking/Communication

	Idle mode: 100 mW (WLAN unassociated)	
	Radio off: 100 mW (WLAN unassociated)	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity Note: Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).	802.11g:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps) 802.11b:-95 dBm (1 Mbps), -93 dBm (2 Mbps), -91 dBm (5.5 Mbps), -88 dBm (11 Mbps) 802.11g:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps)	
Antenna Connections	2 U.FL type connectors (output impedance of 50 ± 2 ohms)	
Form Factors	PCI-Express Half-MiniCard	
Weight	0.0068 lb (3.1 g)	
Dimensions	0.12 x 1.06 x 1.18 in (3.1 x 26.8 x 30.0 mm)	
Operating Voltage	3.3V +/- 9%	
Temperature	**Operating:** **Non-operating:**	14° to 158° F (-10° to 70° C) -40° to 176° F (-40° to 80° C)
Humidity	**Operating:** **Non-operating:**	10% to 90% (non-condensing) 5% to 90% (non-condensing)
Altitude	**Operating:** **Non-operating:**	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber - Radio OFF; LED White - Radio ON	

Technical Specifications – Audio

High Definition Audio	
Type	Integrated
HD Stereo Codec	Realtek 2-channel ALC221 codec
Audio I/O Ports	Front microphone-In (150-K ohm Input Impedance)
	Rear Line-In/Microphone input (150-K ohm Input Impedance, function is configurable by audio driver)
	Rear Line-Out* (190 ohms Output Impedance, expects at least a 10-K ohm load)
	Front Headphone-Out (0.5 Ohm Output Impedance, expects at least a 32 ohm load) Front Microphone/Headphone jack is re-task able to provide Microphone input, line-in or Headphone output to support connecting two headphones to the front of the system. When configured as a second front headphone output, both front headphone outputs are always driven with the same signal.
	All ports are 3.5mm
Internal Speaker Amplifier	1.5W amplifier for the internal speaker only. External speakers must be powered externally. Rear Line-in audio port is re-taskable as either Line-in or Microphone-In.
Multi-streaming Capable	Multi-streaming can be enabled in the Realtek control panel to allow independent audio streams to be sent to/from the front and rear jacks.
Sampling	8 kHz - 192 kHz
Wavetable Syntheses	Yes – Uses OS soft wavetable
Analog Audio	Yes
# of Channels on Line-Out	Stereo (Left & Right channels)
Internal Speaker	Yes
External Speaker Jack	Yes

Technical Specifications - Input/Output Devices

HP PS/2 Keyboard		
Physical Characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	18.22 x 6.47 x 1.1 in (46.28 x 16.43 x 2.79 cm)
	Weight	2 lb (0.9 kg) minimum
Electrical	Operating voltage	+ 5VDC ± 10%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	PS/2 6-pin mini din connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
	Keycaps	Low-profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
Environmental	Acoustics	50-dBA maximum sound pressure level
	Operating temperature	32° to 104° F (0° to 40° C)
	Non-operating temperature	-22° to 149° F (-30° to 65° C)
	Operating humidity	15% to 80% (non-condensing at ambient)
	Non-operating humidity	15% to 90% (non-condensing at ambient)
	Operating shock	N/A
	Non-operating shock	65 inch 2.9 ms, six surface; 30g 266 inch/second; 50g 266 inch/second six surface
	Operating vibration	2-g peak acceleration

Technical Specifications - Input/Output Devices

	Non-operating vibration	Starting at 5 Hz, vary the frequency of vibration from 5 to 500 Hz and back to 5 Hz at a Logarithmic sweep rate of 1 octave per minute.
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	29.93 in (76 cm) on concrete, 16-drop sequence
Approvals	CUL, ICES-003 Class B, FCC, CE Mark,TUV GS, VCCI, BSMI, C-Tick, KC	
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS	

HP USB Smart Card (CCID) Keyboard		
Key Benefits:	• Protects against unauthorized access with smart card technology • Delivers even greater security when combined with a HP ProtectTools smart card and the HP ProtectTools Security Software • Combination of username and password or pin with a smart card or security token • Secures online transactions using digital signatures and certificates • Conforms to industry standards for ease of setup and use • Delivers long product life and quiet operation with high-impact materials and lubricated keys • Spill drain feature	
Physical Characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country
	Form factor	USB basic smart card keyboard
	Colors	Carbonite/Silver
	Dimensions (H x W x D)	18.2 x 6.3 x 1.3 in (46.3 x 16.1 x 3.3 cm)
	Weight	2 lb (0.9 kg) minimum
Electrical	Operating voltage	+ 5VDC ± 5%
	Power consumption	100-mA maximum (with four LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
Mechanical	Languages	30+ available

Technical Specifications - Input/Output Devices

	Keycaps	Standard design
	Switch actuation	55 g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
Environmental	Acoustics	43-dBA maximum sound pressure level
	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	20% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence
SmartCard Function	Support	All ISO 7816 smart cards (FIPS 201)
	Interface	Reads from and writes to all ISO7816-1, 2, 3, 4 memory and microprocessor smart cards (T=0, T=1)
	Chipset	SCM STCII
	Standard APIs supported	PC/SC, EMV2000, SET
	Power	USB Port
		Short circuit detection (protects smart card and reader)

Technical Specifications - Input/Output Devices

		Power supply compliant with ISO7816 and EMV (5V, 60 mA)	
		Supports 3-V and 5-V cards	
	Power consumption	100-mA maximum draw	
	Communication	From card	9600 bps to 330,000 bps
		From computer	12 Mbps (USB transfer speed)
	Landing mechanism	Contact device	Friction contact
		Card insertions rating	Up to 100,000 insertion cycles
	Interface modes	CCID protocol	
	Reader performance interface	USB connection	
	Electro-magnetic standards	Europe	2004/108/EC
		USA	USAFCC part 15
Approvals	CE-Mark, UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC, EMV2000, USB-IF		
Ergonomic Compliance	ISO 9241-4, TUVGS		
Kit Contents	Keyboard, I/O Security and Documentation CD, warranty card		

HP USB PS/2 Washable Keyboard

Physical Characteristics	Keys	104 (US) Layout, 105 (EU) layout – depending upon country
	Dimensions (L x W x H)	17.67x 6.62 x 1.38 in (449 x 168 x 35 mm)
	Weight	1.7 lb (0.77 kg) minimum
Electrical	Operating voltage	+ 5VDC ±5%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
Mechanical	Keycaps	Stepped -profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes

Technical Specifications - Input/Output Devices

	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	7 ft (2.2 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
Environmental	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	4° to 149° F (-20° to 65° C)
	Operating humidity	10% to 95% (non-condensing at ambient)
	Non-operating humidity	0% to 95% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence
Operating system support	Windows® 7, Windows Vista, Windows XP Professional	
Approvals	UL, cUL, FCC, CE, TUV GS, VCCI, BSMI, C-Tick, KCC, USB-IF, WHQL, EN/IEC 60601-1, IP66/NEMA4X	
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS	

HP PS/2 Mouse		
Dimensions (H x L x W)	1.46 x 2.48 x 4.53 in (3.70 x 6.29 x 11.50 cm)	
Weight	3.53 oz (100g; +10g/- 5 g)	
Environmental	Operating temperature	-32° to 104°F (0° to 40° C)
	Non-operating temperature	-4° to 140°F (-20° to 60° C)
	Operating humidity	10% to 90% (non condensing at ambient)
	Non-operating humidity	10% to 90% (non condensing at ambient)
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces

Technical Specifications - Input/Output Devices

	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
Electrical	Operating voltage	5 VDC ± 10%
	Power consumption	100mA
	System consumption	PS/2 mini-din connector
	ESD	CE level 4, 15 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC99 - 2001	Functionally compliant
Mechanical	Resolution	800 DPI
	Tracking speed	10 in/s (25.4 cm/s) maximum
	Acceleration	±15%
	Switch actuation	65±20 gf
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	80 km
	Cable length	6 ft (1.8 m)
	Microsoft PC99 - 2001	Mechanically compliant
Scroll wheel	Width	6 mm
	Diameter	22.5 ± 0.2 mm
	Maximum rotation force	50 gf-cm
	Switch type	Light force micro-switch
	Switch life	1 million operations
	Mechanical life	Minimum 200,000 revolutions
Regulatory Approvals	UL/cUL, FCC, CE Mark, TUV/GS, VCCI, KCC, BSMI, C-Tick	

Technical Specifications - Input/Output Devices

HP USB Mouse	
Dimensions (H x L x W)	1.5 x 4.5 x 2.5 in (3.7 x 11.5 x 6.3 cm)
Weight	0.22 lb (0.10 kg)
Cable length	70.9 in (180 cm)
System requirements	Available USB port

HP USB 1000dpi Laser Mouse		
Dimensions (H x L x W)	1.47 x 4.53 x 2.47 in (37.3 x 114.97 x 62.86 mm)	
Weight	3.360 oz (102g)	
Cable length	70.9 in (180 cm)	
System requirements	Available USB port	
Environmental	Operating Temperature	32° to 104° F (0° to 40° C)
	Non-operating Temperature	-4° to 140° F (-20° to 60° C)
	Operating Humidity	10% to 90% (non-condensing at ambient)
Mechanical	Resolution	1000dpi
	Tracking Speed	45 cm/sec
	Cable Length	70.9 in (180 cm)

HP USB PS/2 Washable Mouse		
Dimensions (H x L x W)	1.56 x 2.44 x 4.61 in (3.95 x 6.21 x 11.7 cm)	
Weight	4.44 oz (126 g)	
Environmental	Operating temperature	–32° to 104°F (0° to 40° C)

Technical Specifications - Input/Output Devices

	Non-operating temperature	–4° to 140°F (–20° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	10% to 90% non-condensing
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
Electrical	Operating voltage	5 VDC ± 10%
	Power consumption	100mA
	System consumption	PS/2 mini-din connector or USB
	ESD	CE level 2 8 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC99 - 2001	Functionally compliant
Mechanical	Resolution	1000 ± 20% DPI
	Tracking speed	14 in/s (35.56 cm/s) maximum
	Acceleration	2 g
	Switch actuation	70 g nominal peak force
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	8.8 ft total 70 cm+ 2m extension
	Cable length	Mechanically compliant

Technical Specifications - Input/Output Devices

	Microsoft PC99 - 2001	1000 ± 20% DPI
Scroll wheel	Width	6 mm
	Diameter	1 in (25.4 mm)
	Maximum rotation force	48 rats/sec
	Switch type	Light force micro-switch
	Switch life	3 million operations
	Mechanical life	Minimum 200,000 revolutions
Regulatory Approvals	FCC, CE Mark, ICES-003-B, IP66/NEMA4X	

Unit Environment and Operating Conditions

General Unit Operating Guidelines

- Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range.
- Leave a 10.2 cm (4 in) clearance on all vented sides of the computer to permit the required airflow.
- Never restrict airflow into the computer by blocking any vents or air intakes.
- Do not stack computers on top of each other or place computers so near each other that they are subject to each other's re-circulated or preheated air.
- Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow.
- If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply.

Temperature Range	Operating: 50° to 95° F (10° to 35° C)* Non-operating: –22° to 140° F(–30° to 60° C)
Relative Humidity	Operating: 10% to 90% (non-condensing at ambient) Non-operating: 5% to 95% (non-condensing at ambient)
Maximum Altitude (unpressurized)	Operating: 10,000 ft (3048 m) Non-operating: 30,000 ft (9144 m)

*Operating temperature is de-rated 1.0 deg C per 300 m (1000 ft) to 3000 m (10,000 ft) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.

Power Supply

	DM	MT	SFF
Standard Efficiency	External 65W active PFC 87% efficient N/A	300W active PFC (230 VAC input only)	240W active PFC
High Efficiency* 80 PLUS Bronze	N/A	300W active PFC EStar 6 82/85/82% efficient at 20/50/100% load (115V) 82/85/82% efficient at 20/50/100% load (230V)	240W active PFC 82/85/82%efficient at 20/50/100% load (115V) 82/85/82% efficient at 20/50/100% load (230V)
Operating Voltage Range	90 - 264 VAC	90 - 264 VAC	90 - 264 VAC
Rated Voltage Range	100 - 240 VAC	200 - 240 VAC (300W active PFC) 100 - 240 VAC	100 - 240 VAC
Rated Line Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Operating Line Frequency	47 – 63 Hz	47 – 63 Hz	47 – 63 Hz
Rated Input Current	N/A	4A	4A
Rated Input Current with Energy Efficient* Power Supply	TBA	4A	4A

Technical Specifications – Power

Current Leakage (NFPA 99)	< 250 µA	<900uA / 230Vac (300W PSU)	< 275 µA @ 120V
Power Supply Fan	N/A	80mm Fan (300W PSU)	70mm Fan
Power cord length	N/A	6.0 ft. (1.83 m)	6.0 ft. (1.83 m)
External Power Adapter			
Dimensions	2.2 x 1.2 x 4.5 in 55 x 30 x 113.5 mm	N/A	N/A
Total Cord Length	12 ft. 8 in	N/A	N/A

*High efficiency power supply is a requirement for ENERGY STAR® certification in conjunction with a select range of processors and modules

Technical Specifications – Weights & Dimensions

Weights & Dimensions

(configured with 1 HDD & 1 ODD)

	DM	MT	SFF
Chassis (W x H x D)	6.9 x 1.3 x 7.0 in 175 x 34 x 177 mm	182.88 X 357 X 402 mm 7.2 x 14.05 x 15.82 in	337 x 100 x 380.5 mm 13.26 x 3.93 x 14.98 in
System Volume	62.79 cu in 1.05 L	26.24 L	12.82 L
System Weight*	2.9 lb 1.3 kg	7.148 kg 15.75 lb	5.905 kg 13.01 lb
Max Supported Weight (desktop orientation)	N/A	N/A	35 kg
Tower Stand (H x W x D)	.77x 4.6 x 6.3 in 19.5 x 117 x 160 mm Weight: 47g/ .1 lbs.	N/A	27.5 x 178.2 x 199 mm 1.08 x 7.01 x 7.83 in
Packaged (H x W x D)	7.8 x 11.4 x 19.7 in 198 x 290 x 500 mm	535 X 289 X 500 mm 21.06 x 11.37 x 19.68 in	528 x 229 x 499 mm 20.78 x 9.01 x 19.64 in 245 x 499 x 599 mm 9.64 x 19.64 x 23.58 in
Shipping Weight	9.0 lb. 4.1 kg	Est. = ~10.7 kg (packaged) ~23.58 lb	Est. = 9.691 kg 21.365lb
Palletization Profile	8-units per layer 10/12 layer max 80/96 per pallet	4-units per layer 8-layer max. 32-units per pallet	SEA 4-units per layer 10-layer max. 32-units per pallet AIR 4-units per layer 5-layer max. 20-units per pallet

Technical Specifications – Miscellaneous Features

Management Features

- Advanced Configuration and Power Management Interface (ACPI). Allows the system to wake from a low power mode. Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
- Intel® Wired for Management support; industry wide initiative to make Intel® architecture based PCs, servers and mobile computers more inherently manageable out-of-the-box and over the network
- Dual State Power Button; acts as both an on/off button and a suspend-to-sleep button

Serviceability Features

- Dual colored power LED on front of computer to indicate either normal or fault condition
- Diagnostic LED Explanation Table:
  - Number of 1-second red LED blinks followed by a 2-second pause, then repeats:
    - 2 - processor thermal protection activated
    - 3 - processor not installed
    - 4 - power supply failure
    - 5 -- memory error
    - 6 - video error
    - 7 - PCA failure (ROM detected failure prior to video)
    - 8 - invalid ROM, boot block recovery mode
    - 9 - system not fetching code
    - 10 - system hang while loading an option ROM
- HP PC Hardware Diagnostics UEFI:
  - This utility enables hardware level testing outside the operating system on many components. The diagnostics can be invoked by pressing F2 at POST, and is available as a download from HP Support
- System/Emergency ROM
- Flash ROM
- CMOS Battery Holder for easy replacement
- Flash Recovery with Video Configuration Record Software
- 5 Aux Power LED on System PCA
- Processor ZIF Socket for easy Upgrade
- Over-Temp Warning on Screen (Requires IM Agents)
- Clear Password Jumper
- DIMM Connectors for easy Upgrade
- Clear CMOS Button
- NIC LEDs (integrated) (Green & Amber)
- Dual Color Power and HD LED - To Indicate Normal Operations and Fault Conditions
- Color coordinated cables and connectors
- Tool-less Hood Removal
- Front power switch
- System memory can be upgraded without removing the system board or any internal components
- Tool-less Hard Drive, CD & Diskette Removal
- Green Pull Tabs, and Quick Release Latches for easy Identification

Additional Features

	Description
Towerable Orientation	Product can be oriented as either a desktop (horizontal) or a tower (vertical)
Drive Lock	Implementation of the industry standard ATA Security feature set. When enabled, it prevents software access to user data on the drive until one or two user-defined passwords are provided.
Drive Protection System	DPS Access through F10 Setup during Boot

Technical Specifications – Miscellaneous Features

	A diagnostic hard drive self test. It scans critical physical components and every sector of the hard drive for physical faults and then reports any faults to the user
	Running independently of the operating system, it can be accessed through a Windows-based diagnostics utility or through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced
	The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types of failures
SMART Technology (Self-Monitoring, Analysis and Reporting Technology)	Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted
SMART I - Drive Failure Prediction	Predicts failures before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count
SMART II - Off-Line Data Collection	By avoiding actual hard drive failures, SMART hard drives act as "insurance" against unplanned user downtime and potential data loss from hard drive failure
SMART III - Off-Line Read Scanning with Defect Reallocation	IOEDC: I/O Error Detection Circuitry
	Detects errors in Read/Write buffers on HDD cache RAM
SMART IV - End-to-End CRC for hard drives	Interface in F10 setup provides confirmation of SMART IV support.

Technical Specifications – Environmental Data

Environmental Data

Eco-Label Certifications & Declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT Silver registered in the United States. See http://www.epeat.net for registration status in your country.

Small Form Desktop

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Ultra-slim Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Energy Consumption (in accordance with US ENERGY STAR® test method)	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 60Hz**
Normal Operation (Short idle)	24.93 W	24.58 W	24.95 W
Normal Operation (Long idle)	22.42 W	21.21 W	22.29 W
Sleep	1.40 W	1.48 W	1.40 W
Off	0.76 W	0.84 W	0.75 W

NOTE:
Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 60Hz**
Normal Operation (Short idle)	85 BTU/hr	84 BTU/hr	85 BTU/hr
Normal Operation (Long idle)	77 BTU/hr	73 BTU/hr	22 BTU/hr
Sleep	5 BTU/hr	5 BTU/hr	5 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr

***NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.**

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Typically Configured - Idle	3.7	27
Fixed Disk - Random writes	3.6	28

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 10 USB ports
- 2 memory slots
- 1 PCIe x16 (3.0) half-length slot
- 1 PCIe x16 (2.0) (wired as a x4) half-length slot
- 2 PCIe x1 (2.0) half-length slot
- 1 Slim ODD
- 1 3.5” external drive bay; used for installing a Media Card Reader or 2nd data storage drive

Technical Specifications – Environmental Data

- 1 2.5” internal storage drive bay
- 1 3.5” internal storage drive bay

Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:
Mercury greater the1ppm by weight
Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)
Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Silver level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 10.5% post-consumer recycled plastic (by wt.)
- This product is 91.8% recycle-able when properly disposed of at end of life.

Packaging Materials

- External:
  - PAPER/Corrugated 2380 g
- Internal:
  - PLASTIC/EPE (Expanded Polyethylene) 185 g
  - PLASTIC/Polyethylene low density 45 g
  - PLASTIC/Polypropylene 15 g
- The PAPER/Corrugated packaging material is made from 54.7% recycled content.
- The PLASTIC/EPE (Expanded Polyethylene) packaging materials contains at least 19.5% recycled content.
- The PLASTIC/Polyethylene low density packaging materials contains at least 19.5% recycled content.
- The PLASTIC/Polypropylene packaging materials contains at least 5% recycled content.

Common to all Form Factors

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at: http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/qse.pdf):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons

- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report
http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html
Eco-label certifications
http://www8.hp.com/us/en/hp-information/environment/ecolabels.html
ISO 14001 certificates:
http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf
and
http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

Technical Specifications – Environmental Data

Environmental Data

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT Gold registered in the United States. See http://www.epeat.net for registration status in your country.

Microtower

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Tower model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Energy Consumption (in accordance with US ENERGY STAR® test method)	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 60Hz**
Normal Operation (Short idle)	24.93 W	24.58 W	24.95 W
Normal Operation (Long idle)	22.42 W	21.21 W	22.29 W
Sleep	1.40 W	1.48 W	1.40 W
Off	0.76 W	0.84 W	0.75 W

Note:
Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 60Hz**
Normal Operation (Short idle)	85 BTU/hr	84 BTU/hr	85 BTU/hr
Normal Operation (Long idle)	77 BTU/hr	73 BTU/hr	22 BTU/hr
Sleep	5 BTU/hr	5 BTU/hr	5 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L_{WAd}, bels)	Sound Pressure (L_{pAm}, decibels)
Typically Configured – Idle	3.7	27
Fixed Disk – Random writes	3.6	28

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 6 USB ports

- 2 memory slots
- 1 Mini PCIe half-length slot
- 1 MXM 3.0 Type A - 35W slot
- 1 mSATA slot
- 1 2.5" internal bay supporting up to Two 2.5" hard drives (HDD/SSD/SED/SSHD)
- 1 5.25" external supporting optical drive

<edit list of features as required>

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:
Mercury greater the1ppm by weight
Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)
Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <gold> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 10.5% post-consumer recycled plastic (by wt.)
- This product is 91.8% recycle-able when properly disposed of at end of life.

Packaging Materials

External:	PAPER/Corrugated	2380 g
Internal:	PLASTIC/EPE (Expanded Polyethylene)	185 g
	PLASTIC/Polyethylene low density	45 g
	PLASTIC/Polypropylene	15 g

The PAPER/Corrugated packaging material contains at least 54.7 % recycled content.
The PLASTIC/EPE (Expanded Polyethylene) packaging materials contains at least 19.5% recycled content.
The PLASTIC/Polyethylene low density packaging materials contains at least 19.5% recycled content.
The PLASTIC/Polypropylene packaging materials contains at least 19.5% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/qse.pdf):

- Asbestos
- Certain Azo Colorants

- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Technical Specifications – Environmental Data

Hewlett-Packard Corporate Environmental Information	For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications http://www8.hp.com/us/en/hp-information/environment/ecolabels.html ISO 14001 certificates: http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

Change Log

Communication Devices	DM	MT	SFF	Part Number
Intel® Ethernet I210 – T1 Gbe NIC		X	X	E0X95AA
Intel® 6205 802.11 a/b/g/n PCIe x1 NIC		X	X	E0X93AA
HP WLAN 802.11 a/g/n 2x2 DualBand PCIe x1 Card		X	X	J5C51AA
Intel 7260 802.11 a/b/g/n PCIe x1 Card		X	X	F2P07AA

Graphics Solutions	DM	MT	SFF	Part Number
AMD Radeon™ HD 8350 Graphics (PCIe x16)		X	X	E1C63AA
AMD Radeon™ HD 8490 Graphics Card		X	X	E1C64AA
NVIDIA® NVS™ 310 Graphics (PCIe x16)		X	X	A7U59AA
NVIDIA® NVS™ 315 Graphics (PCIe x16)		X	X	E1C65AA
HP DisplayPort Cable Kit	X	X	X	VN567AA
HP DisplayPort To Dual Link DVI-D Adapter	X	X	X	NR078AA
HP DisplayPort To DVI-D Adapter	X	X	X	FH973AA
HP DisplayPort to HDMI 1.4 Adapter	X	X	X	BP937AA
HP DisplayPort to VGA Adapter	X	X	X	AS615AA
HP DMS-59 to Dual DVI Cable			X	DL139A
HP DMS-59 to Dual DisplayPort Adapter			X	XP688AA
HP Dual Output USB Graphics Adapter	X	X	X	C5U89AA
HP USB Graphics Adapter	X	X	X	NL571AA

Data Storage Drives and Accessories	DM	MT	SFF	Part Number
HP 2TB 7200rpm SATA 6.0Gb/s Hard Disk Drive		X	X	TBD
HP 1-TB 7.2K rpm SATA 6.0Gb/s 3.5” Hard Disk Drive		X	X	QK555AA
HP 1-TB 10K rpm SATA 6.0Gb/s 3.5” Hard Disk Drive			X	C2T91AA
HP 500-GB 7.2K rpm SATA 6.0Gb/s 3.5” Hard Disk Drive			X	QK554AA
HP 128Gb SED Opal 2 Solid State Drive Desktop		X	X	G1K24AA
HP 128-GB SATA 3.0Gb/s Solid State Drive		X	X	QV063AA
HP 500-GB SATA 3.0Gb/s Solid State Hybrid Drive		X	X	E1C62AA
HP Slim Removable SATA Hard Drive Enclosure (frame & carrier)		X	X	C1N41AA
HP Slim Removable SATA Hard Drive Enclosure (carrier only)		X	X	AR639AA
HP Chassis (1bay) Security Kit		X		AR639AA
HP Desktop Mini 500GB HDD/ I/O Module	X			K9Q82AA

*Not available in all regions.

Input Devices	DM	MT	SFF	Part Number
HP USB Keyboard	X	X	X	QY776AA
HP USB Smart Card (CCID) Keyboard	X	X	X	E6D77AA
HP USB Keyboard and Mouse Kit	X	X	X	B1T09AA
HP USB and PS/2 Washable Keyboard and Mouse Kit	X	X	X	BU207AA
HP PS/2 Mouse		X	X	QY775AA
HP USB Mouse	X	X	X	QY777AA
HP USB 1000dpi Laser Mouse	X	X	X	QY778AA

Change Log

HP Wireless Keyboard and Mouse Combination*	X	X	X	QY449AA
HP Desktop Mini I/O Expansion Module	X			K9Q84AA

*Keyboard contains 25% post-consumer recycled plastic material

System Memory	DM	MT	SFF	Part Number
HP 4GB DDR3-1600 (PC3-12800) DIMM		X	X	B4U36AA
HP 8GB DDR3-1600 (PC3-12800) DIMM		X	X	B4U37AA
HP 4GB DDR3-1600 (PC3-12800) SODIMM	X			B4U39AA
HP 8GB DDR3-1600 (PC3-12800) SODIMM	X			B4U40AA

Multimedia Devices and Removable Media Storage	DM	MT	SFF	Part Number
HP Slim DVD-ROM Drive			X	VP033AA
HP Slim SuperMulti DVD Writer Drive			X	QS209AA
HP USB HD 720P v2 Business Webcam	X	X	X	D8Z08AA
HP Business Headset	X	X	X	QK550AA
HP Business Speakers	X	X	X	D9J19AA
HP 14-in-1 Media Card Reader		X	X	E5G19AA
HP 15-in-1 Media Card Reader		X	X	F4N90AA
HP Desktop Mini DVD Super Multi-Writer ODD Expansion Module	X			K9Q83AA

Security Devices	DM	MT	SFF	Part Number
HP SFF Wall Mount/Security Sleeve			X	VN570AA
HP UltraSlim Cable Lock	X	X	X	H4D73AA
HP Desktop Mini Security/Dual VESA Sleeve	X			G1K22AA

Stands and Accessories	DM	MT	SFF	Part Number
Integrated Work Center for Desktop Mini and Thin Client	X			G1V61AA
HP Integrated Work Center Stand for Ultra Slim Desktop and Thin Client	X			E8H16AA
HP DM Chassis Tower Stand	X			G1K23AA
HP Integrated Work Center Stand (SFF)			X	QP897AA
HP SFF Tower Stand			X	VN569AA
HP 400 Tower Bezel Kit		X		E1C66AA
HP 400 SFF Bezel Kit			X	E3F27AA
HP Serial Port Adapter (RS-232 compatible)		X	X	PA716A
HP Parallel Port Kit		X	X	KD061AA
HP USB to Serial Adapter	X	X	X	EM449AA
HP USB to Serial Port Adapter	X			J7B60AA
HP Desktop Mini Rack Mount Module	X			G1K21AA
HP Quick Release Mount Kit	X			EM870AA
ProDisplay Companion Stand	X			J7V21AA
HP Single Monitor Arm	X	X	X	BT861AA
HP Dual Display Stand	X	X	X	AW664AA

Change Log

Business Monitors	DM	MT	SFF	Part Number
HP ProDisplay P191	X	X	X	C9E54AA
HP ProDisplay P201	X	X	X	C9F26AA
HP ProDisplay P221	X	X	X	C9E49AA
HP EliteDisplay E201	X	X	X	C9V73AA
HP EliteDisplay E221	X	X	X	C9V76AA
HP EliteDisplay E231	X	X	X	C9V75AA
HP LA2405x	X	X	X	D0P36AA
HP EliteDisplay E271i	X	X	X	D7Z72AA
HP EliteDisplay E221c	X	X	X	D9E49AA
HP L2206tm	X	X	X	B0L55AA
HP EliteDisplay S231d 23-in IPS LED BLU Notebook Docking Monitor	X			F3J72AA

LANDesk Software (E-Delivery)

Contact your HP representative for available options.

© Copyright 2014 Hewlett-Packard Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are U.S. registered trademarks of the Microsoft group of companies. Intel and Core are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. AMD and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a registered trademark of its proprietor used by Hewlett-Packard Company under license. NVIDIA, GeForce, GRID, Kepler and NVS are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited. DTS, the Symbol, & DTS and the Symbol together are registered trademarks, and DTS Studio Sound is a trademark of DTS, Inc. © DTS, Inc. All Rights Reserved.

December 2014